

E2B-S08KN02-WP-B1 5M

E2B-S08KN02-WP-B1 5M Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



E2B-S08KN02-WP-B1 5M Specifications

Manufacturer Part Number E2B-S08KN02-WP-B1 5M Manufacturer Omron Automation and Safety Category Sensors, Transducers Proximity Sensors Proximity Sensors Package Cylinder, Threaded - M8 Series E2B Sensor Type Inductive Sensing Distance 0.079" (2mm) Output Type PNP-NO, 3-Wire Response Frequency IkHz Shielding Unshielded Voltage - Supply 10 V ~ 30 V Termination Style Cable Leads Operating Temperature -25°C ~ 70°C Ingress Protection IP67 Indicator LED Package / Case Cylinder, Threaded - M8		
CategorySensors, TransducersProximity SensorsPackageCylinder, Threaded - M8SeriesE2BSensor TypeInductiveSensing Distance0.079" (2mm)Output TypePNP-NO, 3-WireResponse FrequencyIkHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VCoperating Temperature-25°C ~ 70°CIngress ProtectionIEDIndicatorLEDPackage / CaseSylinder, Threaded - M8	Manufacturer Part Number	E2B-S08KN02-WP-B1 5M
Proximity SensorsPackageCylinder, Threaded - M8SeriesE2BSensor TypeInductiveSensing Distance0.079" (2mm)Output TypePNP-NO, 3-WireResponse FrequencyIkHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - SupplyOable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIEDAckage / CaseCylinder, Threaded - M8	Manufacturer	Omron Automation and Safety
PackageCylinder, Threaded - M8SeriesE2BSensor TypeInductiveSensing Distance0.079" (2mm)Output TypePNP-NO, 3-WireResponse FrequencyIkHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature1967IndicatorLEDPackage / CaseCylinder, Threaded - M8	Category	Sensors, Transducers
SeriesE2BSensor TypeInductiveSensing Distance0.079" (2mm)Output TypePNP-NO, 3-WireResponse FrequencyIkHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature.25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8		Proximity Sensors
Sensor TypeInductiveSensing Distance0.079" (2mm)Output TypePNP-NO, 3-WireResponse Frequency1kHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply0 V ~ 30 VTermination StyleCable LeadsOperating TemperaturePF67Ingress ProtectionIEDAnderia - CaseCylinder, Threaded - M8	Package	Cylinder, Threaded - M8
Sensing Distance0.079" (2mm)Output TypePNP-NO, 3-WireResponse FrequencyIkHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Series	E2B
Output TypePNP-NO, 3-WireResponse Frequency1kHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Sensor Type	Inductive
Response FrequencyIkHzResponse FrequencyIkHzShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Sensing Distance	0.079" (2mm)
ShieldingUnshieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Output Type	PNP-NO, 3-Wire
Material - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Response Frequency	1kHz
Voltage - Supply10 V ~ 30 VTermination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Shielding	Unshielded
Termination StyleCable LeadsOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Material - Body	Stainless Steel
Operating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Voltage - Supply	10 V ~ 30 V
Ingress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M8	Termination Style	Cable Leads
IndicatorLEDPackage / CaseCylinder, Threaded - M8	Operating Temperature	-25°C ~ 70°C
Package / Case Cylinder, Threaded - M8	Ingress Protection	IP67
	Indicator	LED
Report errors?	Package / Case	Cylinder, Threaded - M8
		Report errors?

E2B-S08KN02-WP-B1 5M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER



E2B-S08KN02-WP-B1 5M Shipping Methods



If you have any question about E2B-S08KN02-WP-B1 5M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com