

E2FM-X10D1-M1GJ-T 0.3M Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



E2FM-X10D1-M1GJ-T 0.3M Specifications

Manufacturer Part NumberE2FM-X10D1-M1GJ-T 0.3MManufacturerOmron Automation and SafetyCategorySensors, TransducersProximity SensorsProximity SensorsPackageCylinder, Threaded - M30SeriesE2FSensor TypeInductiveSensing Distance0.394" (10mm)Output TypeSoHzResponse FrequencySoHzShieldingStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30		
CategorySensors, TransducersPackageProximity SensorsPackageCylinder, Threaded - M30SeriesE2FSensor TypeInductiveSensing Distance0.394" (10mm)Output TypeNPN-NO, 2-WireResponse FrequencySolHzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Manufacturer Part Number	E2FM-X10D1-M1GJ-T 0.3M
PackageProxinity SensorsPackageCylinder, Threaded - M30SeriesE2FSensor TypeInductiveSensing Distance0.394" (10mm)Output TypeNPN-NO, 2-WireResponse Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIEDPackage / CaseCylinder, Threaded - M30	Manufacturer	Omron Automation and Safety
PackageCylinder, Threaded - M30SeriesE2FSensor TypeInductiveSensing Distance0.394" (10mm)Output TypeNPN-NO, 2-WireResponse Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination Style-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Category	Sensors, Transducers
SeriesE2FSensor TypeInductiveSensing Distance0.394" (10mm)Output TypeNPN-NO, 2-WireResponse Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature.25°C ~ 70°CIngress ProtectionIF67IndicatorLEDPackage / CaseCylinder, Threaded - M30		Proximity Sensors
Sensor TypeInductiveSensing Distance0.394" (10mm)Output TypeNPN-NO, 2-WireResponse Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating TemperatureP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Package	Cylinder, Threaded - M30
ASensing Distance0.394" (10mm)Output TypeNPN-NO, 2-WireResponse Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Series	E2F
Output TypeNPN-NO, 2-WireResponse Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Sensor Type	Inductive
Response Frequency50HzShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Sensing Distance	0.394" (10mm)
ShieldingShieldedMaterial - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Output Type	NPN-NO, 2-Wire
Material - BodyStainless SteelVoltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Response Frequency	50Hz
Voltage - Supply10 V ~ 30 VTermination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Shielding	Shielded
Termination StyleCable with ConnectorOperating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Material - Body	Stainless Steel
Operating Temperature-25°C ~ 70°CIngress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Voltage - Supply	10 V ~ 30 V
Ingress ProtectionIP67IndicatorLEDPackage / CaseCylinder, Threaded - M30	Termination Style	Cable with Connector
IndicatorLEDPackage / CaseCylinder, Threaded - M30	Operating Temperature	-25°C ~ 70°C
Package / Case Cylinder, Threaded - M30	Ingress Protection	IP67
	Indicator	LED
Report errors?	Package / Case	Cylinder, Threaded - M30
		Report errors?

E2FM-X10D1-M1GJ-T 0.3M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

E2FM-X10D1-M1GJ-T 0.3M Payment Methods





If you have any question about E2FM-X10D1-M1GJ-T 0.3M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com