

Heisener.com

# **E32D351CSS602MEE3M**

### E32D351CSS602MEE3M Information

Part Number E32D351CSS602MEE3M

Manufacturer United Chemi-Con

Category Capacitors

**Aluminum Electrolytic Capacitors** 

CAP ALUM 6000UF 20% 350V SCREW **Description** 

Radial, Can - Screw Terminals **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## E32D351CSS602MEE3M Specifications

Manufacturer Part Number         E32D351CSS602MEE3M           Manufacturer         United Chemi-Con           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         U32D           Capacitance         6000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         1.250° (31.75mm)           Size / Dimension         3.000° Dia (76.20mm)           Height - Seated (Max)         5.625" (142.88mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	•	
CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesU32DCapacitance6000µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	E32D351CSS602MEE3M
Package         Radial, Can - Screw Terminals           Series         U32D           Capacitance         6000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         1.250" (31.75mm)           Size / Dimension         3.000" Dia (76.20mm)           Height - Seated (Max)         5.625" (142.88mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	United Chemi-Con
PackageRadial, Can - Screw TerminalsSeriesU32DCapacitance6000µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         U32D           Capacitance         6000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         1.250" (31.75mm)           Size / Dimension         3.000" Dia (76.20mm)           Height - Seated (Max)         5.625" (142.88mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         6000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         -           Lead Spacing         1.250" (31.75mm)           Size / Dimension         3.000" Dia (76.20mm)           Height - Seated (Max)         5.625" (142.88mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C  Operating Temperature -40°C ~ 105°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm)  Size / Dimension 3.000" Dia (76.20mm)  Height - Seated (Max) 5.625" (142.88mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Raistance) -  Ead Spacing Satisfactor Terminals	Series	U32D
Voltage - Rated350 VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	6000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  -Ripple Current - High Frequency  Impedance  Lead Spacing  1.250" (31.75mm)  Size / Dimension  3.000" Dia (76.20mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 105°C  -40°C ~	Voltage - Rated	350V
Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  -40°C ~ 105°C  General Purpose  -  1.25°C  1.25°C  1.25°C  2.20°C  3.00°Dia (76.20mm)  3.00°Dia (76.20mm)  5.625° (142.88mm)  Chassis Mount  Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.000" Dia (76.20mm)  Height - Seated (Max) 5.625" (142.88mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.250" (31.75mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.000" Dia (76.20mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.625" (142.88mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### E32D351CSS602MEE3M Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## E32D351CSS602MEE3M Payment Methods





















### E32D351CSS602MEE3M Shipping Methods













If you have any question about E32D351CSS602MEE3M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com