

Heisener.com

E32D630HLS333QD79M

E32D630HLS333QD79M Information

Part Number E32D630HLS333QD79M

Manufacturer United Chemi-Con

Capacitors Category

Aluminum Electrolytic Capacitors

CAP ALUM 33000UF 63V SCREW **Description**

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E32D630HLS333QD79M Specifications

Manufacturer Part Number E32D630HLS333QD79M Manufacturer United Chemi-Con Category Capacitors Package Radial, Can - Screw Terminals Series U32D Capacitance 33000µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Scries Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Package Radial, Can - Screw Terminals Series U32D Capacitance 33000µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	E32D630HLS333QD79M
Package Radial, Can - Screw Terminals Series U32D Capacitance 33000µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	United Chemi-Con
PackageRadial, Can - Screw TerminalsSeriesU32DCapacitance33000μFTolerance-10%, +30%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.125" (28.58mm)Size / Dimension2.500" Dia (63.50mm)Height - Seated (Max)3.125" (79.38mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series U32D Capacitance 33000μF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 33000µF Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +30% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raid (Max) Radial, Can - Screw Terminals	Series	U32D
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.125" (28.58mm)Size / Dimension2.500" Dia (63.50mm)Height - Seated (Max)3.125" (79.38mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	33000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 1.125" (28.58mm) Size / Dimension 4.2500" Dia (63.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +30%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Polar -40°C ~ 105°C -	Voltage - Rated	63V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 1.125" (28.58mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Rapidance -40°C ~ 105°C Repedance - Repedance - Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.125" (28.58mm) Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance-Lead Spacing1.125" (28.58mm)Size / Dimension2.500" Dia (63.50mm)Height - Seated (Max)3.125" (79.38mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing1.125" (28.58mm)Size / Dimension2.500" Dia (63.50mm)Height - Seated (Max)3.125" (79.38mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.500" Dia (63.50mm) Height - Seated (Max) 3.125" (79.38mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.125" (28.58mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.500" Dia (63.50mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.125" (79.38mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

E32D630HLS333QD79M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E32D630HLS333QD79M Payment Methods



















E32D630HLS333QD79M Shipping Methods













If you have any question about E32D630HLS333QD79M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com