

Heisener.com

E36D201LPN202TCA5M

E36D201LPN202TCA5M Information

Part Number E36D201LPN202TCA5M

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 2000UF 200V SCREW **Description**

Radial, Can - Screw Terminals **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E36D201LPN202TCA5M Specifications

Manufacturer Part Number E36D201LPN202TCA5M Manufacturer United Chemi-Con Category Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 2000µF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	*	
Category Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 2000μF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer Part Number	E36D201LPN202TCA5M
Package Radial, Can - Screw Terminals Series U36D Capacitance 2000µF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer	United Chemi-Con
PackageRadial, Can - Screw TerminalsSeriesU36DCapacitance2000μFTolerance-10%, +50%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series U36D Capacitance 2000µF Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance2000µFTolerance-10%, +50%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis Mount	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Series	U36D
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis Mount	Capacitance	2000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency Impedance Lead Spacing O.875" (22.22mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C - 0.875" (22.22mm) 0.875" (22.22mm) - Chassis Mount	Voltage - Rated	200V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension 0.875" (20.22mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Applications	General Purpose
Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount	Ripple Current - Low Frequency	-
Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - High Frequency	-
Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis Mount	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 4.125" (104.78mm) - Chassis Mount	Lead Spacing	0.875" (22.22mm)
Surface Mount Land Size - Mounting Type Chassis Mount	Size / Dimension	2.000" Dia (50.80mm)
Mounting Type Chassis Mount	Height - Seated (Max)	4.125" (104.78mm)
	Surface Mount Land Size	-
Package / Case Radial Can - Screw Terminals	Mounting Type	Chassis Mount
radia, can below reminas	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

E36D201LPN202TCA5M Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E36D201LPN202TCA5M Payment Methods



















E36D201LPN202TCA5M Shipping Methods













If you have any question about E36D201LPN202TCA5M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com