

Heisener.com

E36D251LPN782TEE3N

E36D251LPN782TEE3N Information

Part Number E36D251LPN782TEE3N

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 7800UF 250V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E36D251LPN782TEE3N Specifications

Manufacturer Part Number E36D251LPN782TEE3N Manufacturer United Chemi-Con Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 7800μF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" bia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 7800µF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	E36D251LPN782TEE3N
PackageRadial, Can - Screw TerminalsSeriesU36DCapacitance7800μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	United Chemi-Con
Package Radial, Can - Screw Terminals Series U36D Capacitance 7800µF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series U36D Capacitance 7800µF Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance7800μFTolerance-10%, +50%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing1.250" (31.75mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)5.625" (142.88mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Rated (Max) Rational Size - Radial, Can - Screw Terminals	Series	U36D
Voltage - Rated 250V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	7800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -40°C ~ 85°C	Voltage - Rated	250V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 1.250" (31.75mm) Size / Dimension Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing 1.250" (31.75mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 5.625" (142.88mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.250" (31.75mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.000" Dia (76.20mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.625" (142.88mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

E36D251LPN782TEE3N Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E36D251LPN782TEE3N Payment Methods





















E36D251LPN782TEE3N Shipping Methods













If you have any question about E36D251LPN782TEE3N, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com