

Heisener.com

E36D750HPN233TCA5M

E36D750HPN233TCA5M Information

Part Number E36D750HPN233TCA5M

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 23000UF 75V SCREW **Description**

Radial, Can - Screw Terminals **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E36D750HPN233TCA5M Specifications

Manufacturer Part Number E36D750HPN233TCA5M Manufacturer United Chemi-Con Category Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 23000µF Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 23000µF Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	E36D750HPN233TCA5M
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series U36D Capacitance 23000µF Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	United Chemi-Con
PackageRadial, Can - Screw TerminalsSeriesU36DCapacitance23000μFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series U36D Capacitance 23000µF Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance23000µFTolerance-10%, +50%Voltage - Rated75VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance -10%, +50% Voltage - Rated 75V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	U36D
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 30.875" (22.22mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Capacitance	23000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 0.875" (22.22mm) Size / Dimension 4.125" (104.78mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	-10%, +50%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -40°C ~ 85°C	Voltage - Rated	75V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Rippedance Lead Spacing 0.875" (22.22mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Rapidance -40°C ~ 85°C Reneral Purpose General Purpose	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 0.875" (22.22mm) Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	-
Lead Spacing0.875" (22.22mm)Size / Dimension2.000" Dia (50.80mm)Height - Seated (Max)4.125" (104.78mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.000" Dia (50.80mm) Height - Seated (Max) 4.125" (104.78mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.875" (22.22mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.000" Dia (50.80mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.125" (104.78mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

E36D750HPN233TCA5M Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E36D750HPN233TCA5M Payment Methods



















E36D750HPN233TCA5M Shipping Methods













If you have any question about E36D750HPN233TCA5M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com