

E3FB-LP12 2M

E3FB-LP12 2M Information

, Industrial PNP,PW ime, please contact
Request a Quote
PNP,PW ime, please contact

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



E3FB-LP12 2M Specifications

ManufacturerOmron Automation and SafetyCategorySensors, TransducersOptical Sensors - Photoelectric, IndustrialPackage-SeriesE3FBSensing MethodReflective, Background SuppressionSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time500µsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodEEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixed		
CategorySensors, TransducersOptical Sensors - Photoelectric, IndustrialPackagePackageSeriesSensing MethodReflective, Background SuppressionSensing DistanceVoltage - Supply10 V ~ 30 VResponse TimeSolupatOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodIBC IP67, IP69KCable LengthLight SourceAdjustment TypeOperating Temperature-25°C ~ 55°C	Manufacturer Part Number	E3FB-LP12 2M
Optical Sensors - Photoelectric, IndustrialPackage-SeriesE3FBSensing MethodReflective, Background SuppressionSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time500µsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodIEC IP67, IP69KIngress ProtectionFK240" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Manufacturer	Omron Automation and Safety
Package-SeriesE3FBSensing MethodReflective, Background SuppressionSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time500μsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Category	Sensors, Transducers
SeriesE3FBSensing MethodReflective, Background SuppressionSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time500µsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C		Optical Sensors - Photoelectric, Industrial
Sensing MethodReflective, Background SuppressionSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time500µsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Package	-
Sensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time500μsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Series	E3FB
Voltage - Supply10 V ~ 30 VResponse Time500µsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Sensing Method	Reflective, Background Suppression
Response Time500µsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Sensing Distance	7.874" (200mm)
Output ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Voltage - Supply	10 V ~ 30 V
Connection MethodCableIngress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Response Time	500µs
Ingress ProtectionIEC IP67, IP69KCable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Output Configuration	PNP - Dark-ON/Light-ON - Selectable
Cable Length78.740" (2000.00mm)Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Connection Method	Cable
Light SourceRed LEDAdjustment TypeFixedOperating Temperature-25°C ~ 55°C	Ingress Protection	IEC IP67, IP69K
Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Cable Length	78.740" (2000.00mm)
Operating Temperature $-25^{\circ}\text{C} \sim 55^{\circ}\text{C}$	Light Source	Red LED
	Adjustment Type	Fixed
Report errors?	Operating Temperature	-25°C ~ 55°C
		Report errors?

E3FB-LP12 2M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

E3FB-LP12 2M Payment Methods



E3FB-LP12 2M Shipping Methods



If you have any question about E3FB-LP12 2M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com