

# E3FZ-LS84H 2M

## E3FZ-LS84H 2M Information

Heisener.com	Part Number Manufacturer Category Description Package	E3FZ-LS84H 2M Omron Automation and Safety Sensors, Transducers Optical Sensors - Photoelectric, Industrial SENSOR PHOTO HORIZ BGS 200MM PNP - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# E3FZ-LS84H 2M Specifications

ManufacturerOmron Automation and SafetyCategorySensors, TransducersOptical Sensors - Photoelectric, IndustrialPackage-SeriesE3FZSensing MethodReflective, DiffuseSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodEIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixed		
CategorySensors, TransducersOptical Sensors - Photoelectric, IndustrialPackage-SeriesE3FZSensing MethodReflective, DiffuseSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Manufacturer Part Number	E3FZ-LS84H 2M
Optical Sensors - Photoelectric, IndustrialPackage-SeriesE3FZSensing MethodReflective, DiffuseSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Manufacturer	Omron Automation and Safety
Package-SeriesE3FZSensing MethodReflective, DiffuseSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Category	Sensors, Transducers
SeriesE3FZSensing MethodReflective, DiffuseSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C		Optical Sensors - Photoelectric, Industrial
Sensing MethodReflective, DiffuseSensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Package	-
Sensing Distance7.874" (200mm)Voltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Series	E3FZ
Voltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Sensing Method	Reflective, Diffuse
Response TimeImsOutput ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Sensing Distance	7.874" (200mm)
Output ConfigurationPNP - Dark-ON/Light-ON - SelectableConnection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Voltage - Supply	10 V ~ 30 V
Connection MethodWireIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Response Time	1ms
Ingress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Output Configuration	PNP - Dark-ON/Light-ON - Selectable
Cable Length-Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Connection Method	Wire
Light SourceInfrared (660nm)Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Ingress Protection	IEC IP67, IP69K
Adjustment TypeFixedOperating Temperature-25°C ~ 55°C	Cable Length	-
Operating Temperature $-25^{\circ}\text{C} \sim 55^{\circ}\text{C}$	Light Source	Infrared (660nm)
	Adjustment Type	Fixed
Report errors?	Operating Temperature	-25°C ~ 55°C
		Report errors?

#### E3FZ-LS84H 2M Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## E3FZ-LS84H 2M Payment Methods



# E3FZ-LS84H 2M Shipping Methods



If you have any question about E3FZ-LS84H 2M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com