

## E3ZM-CL62H-M1TJ 0.3M Information

Heisener.com	E3ZM-CL62H-M1TJ 0.3M Omron Automation and Safety Sensors, Transducers Optical Sensors - Photoelectric, Industrial SENSOR PHOTOELECTR 10-150MM M12 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# E3ZM-CL62H-M1TJ 0.3M Specifications

ManufacturerOmron Automation and SafetyCategorySensors, TransducersOptical Sensors - Photoelectric, IndustrialPackage-SeriesE3ZMSensing MethodRetroreflectiveSensing Distance0.394" ~ 5.9" (10mm ~ 150mm) ADJVoltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationConnectorConnection MethodEIC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-		
CategorySensors, TransducersOptical Sensors - Photoelectric, IndustrialPackage-SeriesE3ZMSensing MethodRetroreflectiveSensing Distance0.394" ~ 5.9" (10mm ~ 150mm) ADJVoltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Manufacturer Part Number	E3ZM-CL62H-M1TJ 0.3M
Optical Sensors - Photoelectric, IndustrialPackage-SeriesE3ZMSensing MethodRetroreflectiveSensing Distance0.394" ~ 5.9" (10mm ~ 150mm) ADJVoltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Manufacturer	Omron Automation and Safety
Package-SeriesE3ZMSensing MethodRetroreflectiveSensing Distance0.394" ~ 5.9" (10mm ~ 150mm) ADJVoltage - Supply10 V ~ 30 VResponse TimeImsOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Category	Sensors, Transducers
SeriesE3ZMSensing MethodRetroreflectiveSensing Distance $0.394" \sim 5.9"(10mm \sim 150mm)$ ADJVoltage - Supply $10 V \sim 30 V$ Response TimeImsOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature $-25°C \sim 55°C$		Optical Sensors - Photoelectric, Industrial
Sensing MethodRetroreflectiveSensing Distance0.394" ~ 5.9" (10mm ~ 150mm) ADJVoltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Output Temperature-25°C ~ 55°C	Package	-
Sensing Distance0.394" ~ 5.9" (10mm ~ 150mm) ADJVoltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Series	E3ZM
Voltage - Supply10 V ~ 30 VResponse Time1msOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Sensing Method	Retroreflective
Response TimeImsOutput ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Sensing Distance	0.394" ~ 5.9" (10mm ~ 150mm) ADJ
Output ConfigurationNPN - Dark-ON/Light-ON - SelectableConnection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Voltage - Supply	10 V ~ 30 V
Connection MethodConnectorIngress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Response Time	lms
Ingress ProtectionIEC IP67, IP69KCable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Output Configuration	NPN - Dark-ON/Light-ON - Selectable
Cable Length-Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Connection Method	Connector
Light SourceInfrared (660nm)Adjustment Type-Operating Temperature-25°C ~ 55°C	Ingress Protection	IEC IP67, IP69K
Adjustment Type-Operating Temperature-25°C ~ 55°C	Cable Length	-
Operating Temperature $-25^{\circ}\text{C} \sim 55^{\circ}\text{C}$	Light Source	Infrared (660nm)
	Adjustment Type	-
Report errors?	Operating Temperature	-25°C ~ 55°C
		Report errors?

### E3ZM-CL62H-M1TJ 0.3M Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### E3ZM-CL62H-M1TJ 0.3M Payment Methods





If you have any question about E3ZM-CL62H-M1TJ 0.3M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com