



EAHP3030WA0 Information

Heisener.com

Part Number EAHP3030WA0

Manufacturer Everlight Electronics Co Ltd

Category Optoelectronics

LED Lighting - White

Description LED WARM WHITE 2725K 80CRI 1212

Package 1212 (3030 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EAHP3030WA0 Specifications

Manufacturer Part Number Manufacturer Everlight Electronics Co Ltd Optoelectronics LED Lighting - White Package 1212 (3030 Metric) Series - Color White, Warm CCT (K) Flux @ 85°C, Current - Test Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) Lumens/Watt @ Current - Test CRI (Color Rendering Index) Current - Max Viewing Angle Mounting Type Package / Case 1212 (3030 Metric) Surface Mount 1212 (3030 Metric)	*	
Category Optoelectronics LED Lighting - White Package 1212 (3030 Metric) Series - Color White, Warm CCT (K) 2725K Flux @ 85°C, Current - Test - Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Manufacturer Part Number	EAHP3030WA0
LED Lighting - White	Manufacturer	Everlight Electronics Co Ltd
Package 1212 (3030 Metric) Series - Color White, Warm CCT (K) 2725K Flux @ 85°C, Current - Test - Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Category	Optoelectronics
Series - Color White, Warm CCT (K) 2725K Flux @ 85°C, Current - Test - Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount		LED Lighting - White
Color White, Warm CCT (K) 2725K Flux @ 85°C, Current - Test - Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Package	1212 (3030 Metric)
CCT (K) 2725K Flux @ 85°C, Current - Test - Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Series	-
Flux @ 85°C, Current - Test Flux @ 25°C, Current - Test 101 lm (Typ) Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) Current - Max 240mA Viewing Angle Mounting Type Surface Mount	Color	White, Warm
Flux @ 25°C, Current - Test Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) Current - Max 240mA Viewing Angle Mounting Type Surface Mount	CCT (K)	2725K
Current - Test 150mA Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Flux @ 85°C, Current - Test	-
Voltage - Forward (Vf) (Typ) 6.4V Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Flux @ 25°C, Current - Test	101 lm (Typ)
Lumens/Watt @ Current - Test 105 lm/W CRI (Color Rendering Index) 80 Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Current - Test	150mA
CRI (Color Rendering Index) Current - Max 240mA Viewing Angle Mounting Type Surface Mount	Voltage - Forward (Vf) (Typ)	6.4V
Current - Max 240mA Viewing Angle 120° Mounting Type Surface Mount	Lumens/Watt @ Current - Test	105 lm/W
Viewing Angle 120° Mounting Type Surface Mount	CRI (Color Rendering Index)	80
Mounting Type Surface Mount	Current - Max	240mA
	Viewing Angle	120°
Package / Case 1212 (3030 Metric)	Mounting Type	Surface Mount
	Package / Case	1212 (3030 Metric)
Supplier Device Package 3030	Supplier Device Package	3030
Size / Dimension 0.118" L x 0.118" W (3.00mm x 3.00mm)	Size / Dimension	0.118" L x 0.118" W (3.00mm x 3.00mm)
Height - Seated (Max) 0.033" (0.83mm)	Height - Seated (Max)	0.033" (0.83mm)
Report errors?		Report errors?

EAHP3030WA0 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EAHP3030WA0 Payment Methods



















EAHP3030WA0 Shipping Methods













If you have any question about EAHP3030WA0, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com