

EB43-S0C256XF

EB43-S0C256XF Information

Heisener.com	Part Number Manufacturer Category Description Package	EB43-S0C256XF Vishay Dale Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 50POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EB43-S0C256XF Specifications

Manufacturer Part Number EB43-S0C256XF Manufacturer Vishay Dale Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Card Edge Connectors - Edgeboard Connectors Package - Stries EB4 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.100" (2.54mm) Number of Rows 2 Pitch Stolder Mounting Type Through Hole Contact Material Solder Contact Finish Thickness Gold Contact Finish Thickness Gold Contact Finish Thickness - Contact Finish Thickness Contilever Contact Finish Thickness Contaliver Color Back Contact Finish Thickness Female Contact Specture Fush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Cobart Type	•		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-SeriesEB4Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100" (2.54mm)Features-Nouning TypeThrough HoleContact FinishSolderContact Finish Thickness-Contact Finish Thickness-ColorBlackFinage FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	EB43-S0C256XF	
Card Edge Connectors - Edgeboard ConnectorsPackage-SeriesEB4Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness-Contact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Vishay Dale	
Package-SeriesEB4Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFolderContact MaterialSolderContact FinishGoldContact Finish Thickness-Contact Finish Thickness-Coltact TypeCantileverColtact TypeBackFolge FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
SeriesEB4Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness-Contact Finish Thickness-Contact Finish Thickness-Contact Finish Thickness-Contact Finish Thickness-ColarBlackFinige FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions0.054" ~ 0.071" (1.37mm ~ 1.80mm)Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeOnlog (2.54mm)Contact MaterialSolderContact FinishSolderContact Finish Thickness-Contact Finish Thickness-Contact Finish Thickness-Contact Finish Thickness-ColorBackFange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-	Package	-	
GenderFenaleNumber of Positions/Bay/Row55Number of Positions0054° ~ 0.071° (1.37mm ~ 1.80mm)Card Thickness0.054° ~ 0.071° (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeMolo (2.54mm)TerminationSolderContact MaterialSolderContact FinishGoldContact Finish-Contact TypeSaleContact TypeSaleContact TypeSaleFinishSaleContact TypeSaleFinishSaleColarSaleFinishSaleColarSaleFinishSaleColarSaleColarSaleFinishSaleColarSaleColarSaleFinishSaleColarSaleFinishSaleColarSale <td>Series</td> <td>EB4</td> <td></td>	Series	EB4	
Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness - Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 50 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness - Contact Type Cantilever Flange Feature Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female	
Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	25	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange Feature-65°C ~ 125°C	Number of Positions	50	
Pich0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.054" ~ 0.071" (1.37mm ~ 1.80mm)	
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-5°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	-	
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Cantilever	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

EB43-S0C256XF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EB43-S0C256XF Payment Methods



EB43-S0C256XF Shipping Methods



If you have any question about EB43-S0C256XF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com