



## **EB63-S1R154XF Information**

Heisener.com

Part Number EB63-S1R154XF
Manufacturer Vishay Dale

Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 30POS 0.125

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ED(2	Q1D1	F 437T	C	• •
FR03.	-81K)	154XF	Specii	ications

Manufacturer Part Number       EB63-S1R154XF         Manufacturer       Vishay Dale         Category       Connectors, Interconnects         Package       -         Series       EB6         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       15         Number of Positions       30         Card Thickness       0.054" ~ 0.071" (1.37mm ~ 1.80mm)         Number of Rows       2         Pitch       0.125" (3.18mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Type       Cantilever         Color       Black         Flange Feature       Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C	EB05-51K134XI Specifications		
Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors  Package - Series EB6 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 15 Number of Positions 30 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness - Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	EB63-S1R154XF	
Card Edge Connectors - Edgeboard Connectors  Package - Series EB6 Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 15 Number of Positions 30 Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness - Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature	Manufacturer	Vishay Dale	
Package-SeriesEB6Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
SeriesEB6Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row15Number of Positions30Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	EB6	
Number of Positions/Bay/Row15Number of Positions30Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm)  Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness - Contact Type Cantilever Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature	Gender	Female	
Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm)  Number of Rows 2  Pitch 0.125" (3.18mm)  Features - Mounting Type Through Hole, Right Angle  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness - Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Number of Positions/Bay/Row	15	
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	30	
Pitch 0.125" (3.18mm)  Features -  Mounting Type Through Hole, Right Angle  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness -  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Card Thickness	0.054" ~ 0.071" (1.37mm ~ 1.80mm)	
Features  Mounting Type Through Hole, Right Angle  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness - Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeCantileverColorBlackFlange FeatureFlush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)	
Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness -  Contact Type Cantilever  Color Black  Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Features	-	
Contact Material  Contact Finish  Gold  Contact Finish Thickness  -  Contact Type  Cantilever  Color  Black  Flange Feature  Operating Temperature  Phosphor Bronze  Gold  Cold  Cold  Phosphor Bronze  Cold  Cold  Contact Type  Cantilever  Cantilever  Cantilever  Cantilever  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature	Mounting Type	Through Hole, Right Angle	
Contact Finish Contact Finish Thickness - Contact Type Cantilever  Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness  Contact Type  Cantilever  Color  Black  Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact Type  Color  Black  Flange Feature  Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C	Contact Finish	Gold	
Color Black Flange Feature Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	-	
Flange Feature Flush Mount, Top Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Cantilever	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
•			Report errors?

## EB63-S1R154XF Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# EB63-S1R154XF Payment Methods



















# EB63-S1R154XF Shipping Methods













If you have any question about EB63-S1R154XF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com