

# EB72S-SA1840X

uest a Quote

### **EB72S-SA1840X Information**

Part Number	EB72S-SA1840X
Manufacturer	Vishay Dale
Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
Description	CONN EDGE DUAL FMALE 36POS 0.156
Package	-
	For the pricing/inventory/lead time, please contact
	us
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com
	Manufacturer Category Description

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# EB72S-SA1840X Specifications

ManufacturerVishay DaleConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-PackageBB7SCard TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions/Bay/Row054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows0.054" ~ 0.071" (1.37mm ~ 1.80mm)Features0.156" (3.96mm)Features0.156" (3.96mm)Forture functionSolder Eyelet(s)Contact MaterialSolder Specified Specifi	*		
Connectors, Interconnects   Card Edge Connectors - Edgeboard Connectors   Package -   Series EB7S   Card Type Non Specified - Dual Edge   Gender Female   Number of Positions/Bay/Row 18   Number of Positions/Bay/Row 36   Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Panel Mount   Contact Material Solder Eyelet(s)   Contact Finish Gold   Contact Finish Thickness -   Contact Type Full Bellows   Color -   Flange Feature Fush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia   Operating Temperature -5%C ~ 125°C	Manufacturer Part Number	EB72S-SA1840X	
Card Edge Connectors - Edgeboard ConnectorsPackage-SeriesEB7SCard TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness-Contact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFuls Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Manufacturer	Vishay Dale	
Package-SeriesEB7SCard TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Sacard Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFuls Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
SeriesEB75Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountYong TypeSolder Eyelet(s)Contact FinishGoldContact Finish Thickness-Contact TypeFull BellowsContact TypeFull BellowsColor-Flange FeatureFuls Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish Thickness-Contact Finish Thickness-Contact TypeFull BellowsContact Type-Full Bellows-Contact Type-Full Bellows-Color-Funge FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row18Number of Positions36Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Type-Contact TypeFull BellowsColor-Flange FeatureFush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Series	EB7S	
Number of Positions/Bay/Row18Number of Positions36Card Thickness0.054" ~ 0.071" (1.37mm ~ 1.80mm)Number of Rows2Pitch0.156" (3.96mm)Features-Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact Type-Full Bellows-ColorFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 36   Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Panel Mount   Termination Solder Eyelet(s)   Contact Material Gold   Contact Finish Gold   Contact Type Full Bellows   Color -   Flange Feature Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia   Operating Temperature -55°C ~ 125°C	Gender	Female	
Card Thickness 0.054" ~ 0.071" (1.37mm ~ 1.80mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Panel Mount   Termination Solder Eyelet(s)   Contact Material Phosphor Bronze   Contact Finish Gold   Contact Finish Thickness -   Contact Type Full Bellows   Color -   Flange Feature Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia   Operating Temperature -5°C ~ 125°C	Number of Positions/Bay/Row	18	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Number of Positions	36	
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Card Thickness	0.054" ~ 0.071" (1.37mm ~ 1.80mm)	
Features-Mounting TypePanel MountMounting TypeSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Mounting Type	Panel Mount	
Contact FinishGoldContact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Termination	Solder Eyelet(s)	
Contact Finish Thickness-Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColor-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Contact Finish	Gold	
Color-Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Contact Finish Thickness	-	
Flange FeatureFlush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) DiaOperating Temperature-55°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Color	-	
	Flange Feature	Flush Mount, Top Opening, Unthreaded, 0.128" (3.25mm) Dia	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

#### EB72S-SA1840X Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## EB72S-SA1840X Payment Methods



## EB72S-SA1840X Shipping Methods



If you have any question about EB72S-SA1840X, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com