



# **EBA14DRXS Information**

Heisener.com

Part Number EBA14DRXS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 28POS 0.125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **EBA14DRXS Specifications**

Manufacturer Part Number     EBA14DRXS       Manufacturer     Sullins Connector Solutions       Category     Connectors, Interconnects       Package     -       Series     -       Card Type     Non Specified - Dual Edge       Gender     Female       Number of Positions/Bay/Row     14       Number of Positions     28       Card Thickness     0.062" (1.57mm)       Number of Rows     2       Pitch     0.125" (3.18mm)       Features     -       Mounting Type     Through Hole       Termination     Solder       Contact Material     Phosphor Bronze       Contact Finish     Gold       Contact Finish Thickness     10µin (0.25µm)       Contact Type     Full Bellows       Color     -       Flange Feature     Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	EB/114DK/15 Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         14           Number of Positions         28           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	EBA14DRXS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row14Number of Positions28Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         14           Number of Positions         28           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         14           Number of Positions         28           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Full Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row14Number of Positions28Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row14Number of Positions28Card Thickness $0.062" (1.57mm)$ Number of Rows2Pitch $0.125" (3.18mm)$ Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature $-65°C \sim 125°C$	Series	-
Number of Positions/Bay/Row14Number of Positions28Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions       28         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.125" (3.18mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10µin (0.25µm)         Contact Type       Full Bellows         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	14
Number of Rows2Pitch $0.125"$ ( $3.18mm$ )Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ ( $3.18mm$ ) DiaOperating Temperature $-65°C \sim 125°C$	Number of Positions	28
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness 10μin (0.25μm)  Contact Type Full Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125$ " (3.18mm) DiaOperating Temperature $-65$ °C ~ $125$ °C	Pitch	0.125" (3.18mm)
Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-
Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}$ C $\sim 125^{\circ}$ C	Mounting Type	Through Hole
Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Full Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color - Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type  Full Bellows  Color  Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, $0.125$ " (3.18mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **EBA14DRXS** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EBA14DRXS Payment Methods**





















## **EBA14DRXS Shipping Methods**













If you have any question about EBA14DRXS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com