



EBC06DCZB Information

Heisener.com

Part Number EBC06DCZB

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 12POS 0.100

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EBC06DCZB Specifications

Manufacturer Part Number EBC06DCZB Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	EDC00DCZD Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Type Cantilever Color - Flange Feature - Operating Temperature -	Manufacturer Part Number	EBC06DCZB
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row - Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Flange Feature Operating Temperature -65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 12 Card Thickness - Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness-Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Termination-Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Termination - Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Number of Positions	12
Pitch0.100" (2.54mm)Features-Mounting Type-Termination-Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	-
Features-Mounting Type-Termination-Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting Type-Termination-Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
Termination-Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	-
Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Color Color Flange Feature Operating Temperature Gold Gold Contact Type Cantilever	Termination	-
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever $-65^{\circ}C \sim 125^{\circ}C$	Contact Material	Phosphor Bronze
Contact Type Color Color Flange Feature Operating Temperature Cantilever - Cantilever - Contact Type Cantilever - Contact Type Cantilever - Color	Contact Finish	Gold
Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Operating Temperature -65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

EBC06DCZB Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EBC06DCZB Payment Methods





















EBC06DCZB Shipping Methods













If you have any question about EBC06DCZB, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com