



EBC06DKDI Information

Heisener.com

Part Number EBC06DKDI

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 12POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EBC06DKDI Specifications

Manufacturer Part Number EBC06DKDI Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	EBC00DIEDI Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	EBC06DKDI
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature Card Solder 1.50 Card Threaded Tesert, 4-40 Operating Temperature 5.50 Card Card Connectors - Edgeboard Connectors - Edgeboard Connectors - Edgeboard Connectors - Solder Contact Type Cantilever - 65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature 65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	6
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	12
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Cantilever Color - Flange Feature Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature -65° C ~ 125° C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10μin (0.25μm)$ Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature -65 °C ~ 125 °C	Features	-
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μ in $(0.25\mu$ m) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65° C $\sim 125^{\circ}$ C	Mounting Type	Through Hole
Contact Finish Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever $-$ Color $-$ Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color - Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

EBC06DKDI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EBC06DKDI Payment Methods





















EBC06DKDI Shipping Methods













If you have any question about EBC06DKDI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com