

EBC06DPGH

EBC06DPGH Information

Heisener.com	Part Number Manufacturer Category Description Package	EBC06DPGH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 12POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EBC06DPGH Specifications

Manufacturer Part Number EBC06DPGH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Cated Edge Connectors - Edgeboard Connectors Cated Edge Connectors - Edgeboard Connectors Package - Series - Card Type Mon Specified - Data Edge Gender Female Number of Positions/Bay/Row 6 Number of Positions/Bay/Row 6 Number of Positions 12 Young of Positions 2 Number of Rows 2 Number of Rows 2 Young Hole, Right Angle 100° (2.54mm) Young Hole, Right Angle 100° (2.54mm)	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nounging TypeMinghel Hole, Right AngleContact FinishSolderContact FinishGoldContact Finish Thickness10µín (0.25µm)Contact Finish ThicknessInjuin (0.25µm)Contact Finish Thickness10µín (0.25µm)Contact Finish Thickness50°CColor-Fining FeatureTop Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature65°C ~ 125°C	Manufacturer Part Number	EBC06DPGH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Card Thickness0602" (1.57mm)Card Thickness0.662" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type6Contact MaterialSolderContact FinishGoldContact Finish Thickness10jm (0.25µm)Contact Finish ThicknessGoldContact Finish Thickness10jm (0.25µm)Color10prin BellowsColor-Finige FeatureMount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mn)Number of Rows2Pitch0.100" (2.54mn)Features-Mounting Typeronge Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish ThicknessIpin (0.25µm)Contact TypeHairpin BellowsColor-Fange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mn) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeHairin BellowsColor-Flange FeatureGroMountOpening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialPosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHaipin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65° C ~ 125°C	Package	-
Gender Female Number of Positions/Bay/Row 6 Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Condet Hick Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness Gold Contact Finish Thickness Idµin (0.25µm) Color - Flange Feature Solder Contact Finish Thickness Gold Contact Finish Thickness Gold Color - Flange Feature Commute Quencies (0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeHairpin BellowsColor-Flange FeatureContact Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 12 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Mounting TypeSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColor-Flange FeatureGopMount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	6
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	12
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Color-Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphoraencalContact FinishGoldContact Finish ThicknessI/µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors

EBC06DPGH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EBC06DPGH Payment Methods



EBC06DPGH Shipping Methods



If you have any question about EBC06DPGH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com