



## **EBC12DKDS Information**

Heisener.com

Part Number EBC12DKDS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 24POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **EBC12DKDS Specifications**

Manufacturer Part Number         EBC12DKDS           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         12           Number of Positions         24           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	EBC12BIXDS Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         12           Number of Positions         24           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	EBC12DKDS
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         12           Number of Positions         24           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         12           Number of Positions         24           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         12           Number of Positions         24           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
Gender         Female           Number of Positions/Bay/Row         12           Number of Positions         24           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	12
Number of Rows2Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in (0.25 $\mu$ m)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65^{\circ}$ C ~ 125°C	Number of Positions	24
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Contact Finish Thickness 10μin (0.25μm)  Contact Type Cantilever  Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125$ " (3.18mm) DiaOperating Temperature $-65$ °C ~ $125$ °C	Pitch	0.100" (2.54mm)
Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}$ C ~ $125^{\circ}$ C	Features	-
Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness $10μin (0.25μm)$ Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ $125$ °C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever $-$ Color $-$ Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia $-65^{\circ}$ C $\sim 125^{\circ}$ C	Contact Material	Phosphor Bronze
Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **EBC12DKDS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EBC12DKDS Payment Methods**



















### **EBC12DKDS Shipping Methods**













If you have any question about EBC12DKDS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com