

# EBC12DRTI-S13

lest a Quote

#### **EBC12DRTI-S13 Information**

Heisener.com	Part Number	EBC12DRTI-S13
	Manufacturer	Sullins Connector Solutions
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
	Description	CONN EDGE DUAL FMALE 24POS 0.100
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **EBC12DRTI-S13 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGoald Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact Finish ThicknessOidContact Finish ThicknessIujin (0.25µm)Contact TypeFull BellowsContact TypeSulderContact Finish ThicknessIujin (0.25µm)Contact TypeFull BellowsContact TypeSuleContact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsContact TypeSuleContact TypeSuleContact TypeFull BellowsContact TypeSuleContact TypeSuleContact TypeSuleContact TypeSuleContact TypeSuleContact TypeSuleContact TypeSuleContact Type		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSuderContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFinage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C	Manufacturer Part Number	EBC12DRTI-S13
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorBueFinage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish Thickness10µin (0.25µm)Contact TypeFeallewsContact TypeBoard Edge, Straddle MountContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-5°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish ThicknessI0µin (0.25µm)Contact TypeFull BellowsColorBueFage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row12Number of Positions24Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialGoldContact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions     24       Card Thickness     0.062" (1.57mm)       Number of Rows     2       Pitch     0.100" (2.54mm)       Features     Card Extender       Mounting Type     Board Edge, Straddle Mount       Termination     Solder       Contact Material     Gold       Contact Finish Thickness     Gold       Contact Type     Full Bellows       Color     Blue       Flange Feature     Top Mount Opening, Threaded Insert, 4-40       Operating Temperature     -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	12
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	24
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)ColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Blue   Flange Feature Top Mount Opening, Threaded Insert, 4-40   Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **EBC12DRTI-S13 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **EBC12DRTI-S13** Payment Methods



#### **EBC12DRTI-S13** Shipping Methods



If you have any question about EBC12DRTI-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com