



## **EBC20HETH Information**

Heisener.com

Part Number EBC20HETH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 20POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **EBC20HETH Specifications**

Manufacturer Part Number     EBC20HETH       Manufacturer     Sullins Connector Solutions       Category     Connectors, Interconnects       Package     -       Series     -       Card Type     Non Specified - Dual Edge       Gender     Female       Number of Positions/Bay/Row     -       Number of Positions     20       Card Thickness     0.062" (1.57mm)       Number of Rows     1       Pitch     0.100" (2.54mm)       Features     -       Mounting Type     Through Hole       Termination     Solder       Contact Material     Phosphor Bronze       Contact Finish     Gold       Contact Type     Cantiever       Color     -       Flange Feature     Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	EBC2011E111 Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	EBC20HETH
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         20           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row-Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row       -         Number of Positions       20         Card Thickness       0.062" (1.57mm)         Number of Rows       1         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions20Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	20
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type  Through Hole  Termination  Solder  Contact Material  Phosphor Bronze  Contact Finish  Contact Finish Thickness  10μin (0.25μm)  Contact Type  Cantilever  Color  Flange Feature  Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C	Number of Rows	1
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, $0.125$ " (3.18mm) DiaOperating Temperature $-65$ °C ~ $125$ °C	Pitch	0.100" (2.54mm)
Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Unthreaded, $0.125$ " ( $3.18mm$ ) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Features	-
Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Mounting Type	Through Hole
Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever Color - Top Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color -  Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **EBC20HETH Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EBC20HETH Payment Methods**



















### **EBC20HETH Shipping Methods**













If you have any question about EBC20HETH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com