



# **EBC25DKUS Information**

Heisener.com

Part Number EBC25DKUS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 50POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EBC25DKUS Specifications**

Manufacturer Part Number       EBC25DKUS         Manufacturer       Sullins Connector Solutions         Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       25         Number of Positions       50         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	EBC25BIXCS Specifications	
Category Cannectors, Interconnects Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer Part Number	EBC25DKUS
Card Edge Connectors - Edgeboard Connectors  Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Category	Connectors, Interconnects
Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       25         Number of Positions       50         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia		Card Edge Connectors - Edgeboard Connectors
Card Type Gender Female  Number of Positions/Bay/Row 25  Number of Positions 50  Card Thickness 0.062" (1.57mm)  Number of Rows 2  Pitch 0.100" (2.54mm)  Features Mounting Type Through Hole, Right Angle  Termination Solder  Contact Material Phosphor Bronze Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever Color Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Package	-
Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features	Series	-
Number of Positions       25         Number of Positions       50         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions       50         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Gender	Female
Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions/Bay/Row	25
Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Positions	50
Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Cantilever Color Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Pitch	0.100" (2.54mm)
Termination  Contact Material  Phosphor Bronze  Contact Finish  Gold  Contact Finish Thickness  10μin (0.25μm)  Contact Type  Cantilever  Color  Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Features	-
Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       10μin (0.25μm)         Contact Type       Cantilever         Color       -         Flange Feature       Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Mounting Type	Through Hole, Right Angle
Contact Finish  Contact Finish Thickness  10μin (0.25μm)  Contact Type  Cantilever  Color  Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Termination	Solder
Contact Finish Thickness 10μin (0.25μm)  Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Material	Phosphor Bronze
Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	Contact Type	Cantilever
	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-65°C ~ 125°C
Report errors		Report errors?

#### **EBC25DKUS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EBC25DKUS Payment Methods**





















### **EBC25DKUS Shipping Methods**













If you have any question about EBC25DKUS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com