

EBC26DREI-S93

est a Quote

EBC26DREI-S93 Information

| Heisener.com | Part Number | EBC26DREI-S93 | |
|--------------------|--------------|---|--|
| | Manufacturer | Sullins Connector Solutions | |
| | Category | Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors | |
| | Description | CONN EDGE DUAL FMALE 52POS 0.100 | |
| | Package | - | |
| | | For the pricing/inventory/lead time, please contact | |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EBC26DREI-S93 Specifications

| ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Type0.009" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSull Contact TypeContact TypeSull Contact TypeContact TypeSull Contact TypeContact TypeSull Contact TypeContact TypeSull Contact Type <t< th=""><th></th><th></th></t<> | | |
|--|-----------------------------|---|
| CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeSull BellowsContact TypeSull BellowsContact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C | Manufacturer Part Number | EBC26DREI-S93 |
| Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorBlueFlange Feature- 55°C ~ 125°C | Manufacturer | Sullins Connector Solutions |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorBlueFlange Feature-co Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Category | Connectors, Interconnects |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact Finish ThicknessSolder Eyelet(s)Contact Finish Thickness10µin (0.25µm)Contact TypeFeallewsContact TypeSolder Spect(s)Contact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | | Card Edge Connectors - Edgeboard Connectors |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsContact TypeFull BellowsColorBueFaquere ColorTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Package | - |
| GenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C | Series | - |
| Number of Positions/Bay/Row26Number of Positions52Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Card Type | Non Specified - Dual Edge |
| Number of Positions 52 Card Thickness 0.093" (2.36mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Gold Contact Finish Thickness Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C | Gender | Female |
| Card Thickness0.093" (2.36mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Number of Positions/Bay/Row | 26 |
| Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Number of Positions | 52 |
| Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Card Thickness | 0.093" (2.36mm) |
| Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessIoµin (0.25µm)Contact TypeBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C | Number of Rows | 2 |
| Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Pitch | 0.100" (2.54mm) |
| TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Features | - |
| Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Mounting Type | Panel Mount |
| Contact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Termination | Solder Eyelet(s) |
| Contact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Material | Phosphor Bronze |
| Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Finish | Gold |
| Color Blue Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C | Contact Finish Thickness | 10µin (0.25µm) |
| Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C | Contact Type | Full Bellows |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Color | Blue |
| | Flange Feature | Top Mount Opening, Threaded Insert, 4-40 |
| Report errors? | Operating Temperature | -65°C ~ 125°C |
| | | Report errors? |

EBC26DREI-S93 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EBC26DREI-S93 Payment Methods



EBC26DREI-S93 Shipping Methods



If you have any question about EBC26DREI-S93, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com