



# **EBC40HEYS Information**

Heisener.com

Part Number EBC40HEYS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 40POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **EBC40HEYS Specifications**

Manufacturer Part Number     EBC40HEYS       Manufacturer     Sullins Connector Solutions       Category     Connectors, Interconnects       Package     -       Series     -       Card Type     Non Specified - Dual Edge       Gender     Female       Number of Positions/Bay/Row     -       Number of Positions     40       Card Thickness     0.062" (1.57mm)       Number of Rows     1       Pitch     0.100" (2.54mm)       Features     -       Mounting Type     Through Hole       Termination     Solder       Contact Material     Phosphor Bronze       Contact Finish Thickness     10µin (0.25µm)       Contact Type     Cantilever       Color     -       Flange Feature     Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia       Operating Temperature     -65°C ~ 125°C	EBC-1011E 15 Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	EBC40HEYS
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         40           Card Thickness         0.062" (1.57mm)           Number of Rows         1           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Cantilever           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row-Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row-Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows1Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness 0.062" (1.57mm)  Number of Rows 1  Pitch 0.100" (2.54mm)  Features  Mounting Type Through Hole  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness 10µin (0.25µm)  Contact Type Cantilever  Color  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows 1 Pitch 0.100" (2.54mm)  Features - Mounting Type Through Hole Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness 10 $\mu$ in (0.25 $\mu$ m)  Contact Type Cantilever  Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Positions	40
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Contact Finish Thickness 10μin (0.25μm)  Contact Type Cantilever  Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Number of Rows	1
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu$ in $(0.25\mu$ m)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125$ " (3.18mm) DiaOperating Temperature $-65$ °C ~ $125$ °C	Pitch	0.100" (2.54mm)
Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}$ C ~ $125^{\circ}$ C	Features	-
Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness $10μin (0.25μm)$ Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ 125°C	Termination	Solder
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Cantilever $-$ Color $-$ Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia $-65^{\circ}$ C $\sim 125^{\circ}$ C	Contact Material	Phosphor Bronze
Contact Type Cantilever  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Side Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **EBC40HEYS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EBC40HEYS Payment Methods**


































If you have any question about EBC40HEYS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com