

## EBM08DCMS

## **EBM08DCMS** Information

Heisener.com	Part Number Manufacturer Category Description Package	EBM08DCMS Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 16POS 0.156 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **EBM08DCMS Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialPiosphor BronzeContact Finish ThicknessGoldContact TypeHaipin BellowsContact TypeBileFaquere FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaCoperating Temperature.65°C ~ 125°C	-		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.156° (3.96mm)Features-Mounting TypeHrough HoleContact MaterialWire WrapContact FinishGoldContact Finish ThicknessJujin (0.25µm)Contact TypeHaipin BellowsColorBlueFlange FeatureSide Mout Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	EBM08DCMS	
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialWire WrapContact Finish ThicknessGoldContact Finish ThicknessIupin (0.25µm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialWire WrapContact Finish Thickness0.0d2Contact Finish ThicknessIupin (0.25µm)Contact TypeHairpin BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions/Bay/Row16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact FinishOiddContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialKoyspor BronzeContact Finish ThicknessGoldContact Finish ThicknessIopin (0.25µm)Contact TypeBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleContact MaterialPhosphor BronzeContact Finish10µin (0.25µm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeOntog HoleContact MaterialWire WrapContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBueFaquere FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 16   Card Thickness 0.062" (1.57mm)   Number of Rows 2   Pitch 0.156" (3.96mm)   Features -   Mounting Type Through Hole   Contact Material Wire Wrap   Contact Finish Gold   Contact Finish Thickness 10µin (0.25µm)   Contact Type Hairpin Bellows   Color Blue   Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	8	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	16	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness10µin (0.25µm)Contact TypeBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough HoleTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.156" (3.96mm)	
TerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole	
Contact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Wire Wrap	
Contact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	10µin (0.25µm)	
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
			Report errors?

#### **EBM08DCMS** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **EBM08DCMS Payment Methods**



### **EBM08DCMS** Shipping Methods



If you have any question about EBM08DCMS, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com