

ECA-0JM153 Information



For Reference Only

Part Number ECA-0JM153

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 15000UF 20% 6.3V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECA-0JM153 Specifications

Manufacturer Part NumberECA-0JM153ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageRadial, CanSeriesMCapacitance15000µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.7A @ 120HzRipple Current - High Frequency2.89A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)		
Category Capacitors Package Radial, Can Series M Capacitance 15000µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Manufacturer Part Number	ECA-0JM153
PackageRadial, CanSeriesMCapacitance15000μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.7A @ 120HzRipple Current - High Frequency2.89A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)	Manufacturer	Panasonic Electronic Components
Package Radial, Can Series M Capacitance 15000µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Category	Capacitors
Series M Capacitance 15000μF Tolerance ±20% Voltage - Rated 6.3 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)		Aluminum Electrolytic Capacitors
Capacitance 15000μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Series	M
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) 6.3V 6.3V 6.3V 6.3V 6.3V 6.3V 6.3V 6.30" Dia (16.00mm) 1.319" (33.50mm)	Capacitance	15000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing O.295" (7.50mm) Size / Dimension Height - Seated (Max) - 1.319" (33.50mm)	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 2.89A @ 10kHz Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) 2000 Hrs @ 85°C -40°C ~ 85°C Polar Polar -0.40°C ~ 85°C Polar -0.40°C ~ 85°C -0.40°C ~ 85	Voltage - Rated	6.3V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 120Hz Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 2.89A @ 10kHz Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) General Purpose 1.7A @ 120Hz 2.89A @ 10kHz 1.319" (33.50mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 2.89A @ 10kHz Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Polarization	Polar
Ripple Current - High Frequency 2.89A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Applications	General Purpose
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Ripple Current - Low Frequency	1.7A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Ripple Current - High Frequency	2.89A @ 10kHz
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.319" (33.50mm)	Impedance	-
Height - Seated (Max) 1.319" (33.50mm)	Lead Spacing	0.295" (7.50mm)
	Size / Dimension	0.630" Dia (16.00mm)
	Height - Seated (Max)	1.319" (33.50mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

ECA-0JM153 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA-0JM153 Payment Methods



















ECA-0JM153 Shipping Methods













If you have any question about ECA-0JM153, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com