

ECA-1HM220B Information



For Reference Only

Part Number ECA-1HM220B

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECA-1HM220B Specifications

Manufacturer Part Number ECA-1HM220B Manufacturer Panasonic Electronic Components Category Capacitors Package Aluminum Electrolytic Capacitors Package Radial, Can Series M Capacitance 2½F Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - ESR (Equivalent Series Resistance) 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" io (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series M Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 10mA @ 120Hz Ripple Current - High Frequency 17omA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	ECA-1HM220B
PackageRadial, CanSeriesMCapacitance22µFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency170mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Panasonic Electronic Components
Package Radial, Can Series M Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series M Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	M
Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency100mA @ 120HzRipple Current - High Frequency170mA @ 10kHzImpedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -40°C ~ 85°C Folar General Purpose 100mA @ 120Hz 170mA @ 10kHz 170mA	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 100mA @ 120Hz Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 170mA @ 120Hz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency 170mA @ 10kHz Impedance - Lead Spacing 0.079" (2.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance-Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	100mA @ 120Hz
Lead Spacing0.079" (2.00mm)Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.472" (12.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	170mA @ 10kHz
Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.472" (12.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.079" (2.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.472" (12.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

ECA-1HM220B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA-1HM220B Payment Methods



















ECA-1HM220B Shipping Methods













If you have any question about ECA-1HM220B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com