

ECA-2CM4R7 Information



For Reference Only

Part Number ECA-2CM4R7

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 4.7UF 20% 160V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECA-2CM4R7 Specifications

Manufacturer Part NumberECA-2CM4R7ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageRadial, CanSeriesMCapacitance4.7μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency78mA @ 120HzRipple Current - High Frequency132.6mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series M Capacitance 4.7µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors M Capacitors Apple 20% 4.7µF -20% 60V -20% 60V 60V 60V 60V 60V 60V 60V 6
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesMCapacitance 4.7μ FTolerance $\pm 20\%$ Voltage - Rated $160V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $2000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $78\text{mA} @ 120\text{Hz}$ Ripple Current - High Frequency $132.6\text{mA} @ 10\text{kHz}$ Impedance-
PackageRadial, CanSeriesMCapacitance4.7μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency78mA @ 120HzRipple Current - High Frequency132.6mA @ 10kHzImpedance-
SeriesMCapacitance $4.7\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $160V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency 78mA @ 120Hz Ripple Current - High Frequency 132.6mA @ 10kHz Impedance-
Capacitance4.7μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency78mA @ 120HzRipple Current - High Frequency132.6mA @ 10kHzImpedance-
Tolerance ±20% Voltage - Rated 160V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 78mA @ 120Hz Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 78mA @ 120Hz Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Applications General Purpose Ripple Current - Low Frequency 78mA @ 120Hz Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Ripple Current - Low Frequency 78mA @ 120Hz Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Ripple Current - High Frequency 132.6mA @ 10kHz Impedance -
Impedance -
Lead Spacing 0.098" (2.50mm)
Size / Dimension 0.248" Dia (6.30mm)
Height - Seated (Max) 0.480" (12.20mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors?

ECA-2CM4R7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA-2CM4R7 Payment Methods



















ECA-2CM4R7 Shipping Methods













If you have any question about ECA-2CM4R7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com