

ECA-2DM4R7 Information

Part Number ECA-2DM4R7

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 4.7UF 20% 200V RADIAL **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECA-2DM4R7 Specifications

Manufacturer Part Number ECA-2DM4R7 Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series M Capacitance 4.7µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole		
Category Capacitors Package Radial, Can Series M Capacitance 4.7µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	ECA-2DM4R7
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesMCapacitance4.7μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency86mA @ 120HzRipple Current - High Frequency146.2mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Panasonic Electronic Components
Package Radial, Can Series M Capacitance 4.7μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
Series M Capacitance 4.7μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance4.7μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency86mA @ 120HzRipple Current - High Frequency146.2mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency86mA @ 120HzRipple Current - High Frequency146.2mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	M
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency86mA @ 120HzRipple Current - High Frequency146.2mA @ 10kHzImpedance-Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	4.7μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type - Through Hole	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Output Mounting Type Through Hole	Voltage - Rated	200V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 86mA @ 120Hz Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type General Purpose 86mA @ 120Hz 146.2mA @ 10kHz - 146.2mA @ 10kHz 146.2mA @ 10kHz - 146.2mA @ 10k	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 146.2mA @ 10kHz Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance - Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.492" (12.50mm) Surface Mount Land Size - Through Hole	Ripple Current - Low Frequency	86mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	146.2mA @ 10kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 0.492" (12.50mm) - Through Hole	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Through Hole	Height - Seated (Max)	0.492" (12.50mm)
	Surface Mount Land Size	-
Package / Case Radial Can	Mounting Type	Through Hole
Tudiui, Cuii	Package / Case	Radial, Can
Report errors?		Report errors?

ECA-2DM4R7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA-2DM4R7 Payment Methods



















ECA-2DM4R7 Shipping Methods













If you have any question about ECA-2DM4R7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com