

ECA22DCKI

ECA22DCKI Information

Heisener.com	Part Number Manufacturer Category Description Package	ECA22DCKI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 44POS 0.125 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECA22DCKI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions0.062" (1.57mm)Number of Rows0.062" (1.57mm)Features-Number of Rows2Pitch0.125" (3.18mm)Features-Contact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness3µin (0.76µm)Contact TypeLoop BellowsContact TypeSolderseContact TypeSolderse<	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions/Bay/Row0.062" (1.57mm)Number of Rows0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsContact TypeJoy DellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer Part Number	ECA22DCKI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsContact Type-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsContact Type-Flange Feature-Flange Feature-Operating Temperature-Contart Finish-Color-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-6% C~ 125 °C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish ThicknessGoldContact TypeJopin (0.76µm)Contact Type-Flange Feature-Flange Feature-Operating Temperature-Cortact Temperature-Contact Temperature-Contact Type-Contact Type-Contact Type-Color-Color-Color-Color-Contact TypeContact TypeColor-Color <td>Package</td> <td>-</td>	Package	-
GenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 44 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Contact Material Solder Contact Finish Gold Contact Finish Thickness Gold Contact Type Loop Bellows Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	22
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	44
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Color-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Openating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeLoop BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Loop Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$
		Report errors?

ECA22DCKI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA22DCKI Payment Methods



ECA22DCKI Shipping Methods



If you have any question about ECA22DCKI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com