

ECA22DRYN

ECA22DRYN Information

Heisener.com	Part Number Manufacturer Category Description Package	ECA22DRYN Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 44POS 0.125 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECA22DRYN Specifications

ManufacturerSullins Connector SolutionsCardegerConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting Type1010" HoleContact FinishSolderContact Finish ThicknessGoldContact Finish ThicknessSolin (0.76µm)Contact TypeFull BellowsContact TypeSolin (0.76µm)Contact TypeSolin (0.76µm) <t< th=""><th>-</th><th></th></t<>	-	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact Type-Contact Type-Contact Type50°C ~ 125°C	Manufacturer Part Number	ECA22DRYN
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact Type-Flange Feature-Folge Feature-Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact Finish ThicknessSolderContact Finish ThicknessGoldContact TypeFull BellowsColor-Flange Feature-Forger Features-Color-Color-Color-Flange Feature-Operating Temperature-6%C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact FinishSolderContact Finish ThicknessGoldContact Finish ThicknessSipin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColor-Flarge Feature-Operating Temperature-Operating Temperature-Operature	Series	-
Number of Positions/Bay/Row22Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact TypeSupin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-Solor C 125°C-	Card Type	Non Specified - Dual Edge
Number of Positions44Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleContact MaterialSolderContact FinishGoldContact Finish ThicknessSupin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	22
Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Number of Positions	44
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Color-Flange Feature-Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFul BellowsColor-Flange Feature-Operating Temperatures-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Mounting Type	Through Hole
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColor-Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color - Flange Feature - Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange Feature-Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	-
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ECA22DRYN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA22DRYN Payment Methods



ECA22DRYN Shipping Methods



If you have any question about ECA22DRYN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com