



ECA50DRTS Information

Heisener.com

Part Number ECA50DRTS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 100POS .125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECA50DRTS Specifications

Manufacturer Part Number ECA50DRTS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Thickness 30µin (0.76µm) Contact Type Full Bellows Cotor - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Ec. 130DK 15 Specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Full Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	ECA50DRTS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions 100 Card Thickness $0.062"$ ($1.57mm$)Number of Rows2Pitch $0.125"$ ($3.18mm$)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 30μ in (0.76μ m)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ ($3.18mm$) DiaOperating Temperature $-65°C \sim 125°C$		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row50Number of Positions 100 Card Thickness $0.062" (1.57mm)$ Number of Rows2Pitch $0.125" (3.18mm)$ Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature $-65°C \sim 125°C$	Series	-
Number of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	50
Number of Rows2Pitch $0.125"$ ($3.18mm$)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ ($3.18mm$) DiaOperating Temperature $-65°C \sim 125°C$	Number of Positions	100
Pitch0.125" (3.18mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Full Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ ($3.18mm$) DiaOperating Temperature -65 °C ~ 125 °C	Pitch	0.125" (3.18mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeFull BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125"$ ($3.18mm$) DiaOperating Temperature -65 °C ~ 125 °C	Features	-
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Mounting Type	Through Hole
Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Full Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color - Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Full Bellows Color Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ECA50DRTS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECA50DRTS Payment Methods



















ECA50DRTS Shipping Methods













If you have any question about ECA50DRTS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com