

ECC06DTAZ

ECC06DTAZ Information

Heisener.com	Part Number Manufacturer Category Description Package	ECC06DTAZ Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 12POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECC06DTAZ Specifications

Manufacturer Part NumberECC06DTAZManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-SeriesSolutions/Bay/RowGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pictares-Number of Rows6Seriers0.00" (2.54mm)Number of Rows0.010" (2.54mm)FeaturesSolderMounting TypeSolderContact Finish ThicknessSolderContact Finish ThicknessSolderContact Finish ThicknessSoluti (0.76µm)Contact Finish ThicknessSoluti (0.76µm)Contact Finish ThicknessSoluti (0.76µm)Color-Fange FeatureFinisMount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaColor-Color-Color-Fanage FeatureSich Cato Cato Cato Cato Cato Cato Cato Cato	-		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness30µi (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65° ~ 125°C	Manufacturer Part Number	ECC06DTAZ	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions/Bay/Row12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type6Contact MaterialSolderContact FinishGoldContact FinishGoldContact Finish Thickness30µi (0.76µm)Color-Flange FeatureLoop BellowsColor-Finage FeatureFinish Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65° < 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeFolder Allen Allen AllenContact MaterialSolderContact FinishGoldContact FinishGoldContact Finish ThicknessJojin (0.76µm)Color-Flange FeatureFlange Neurolet Allen A	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialPosphor BronzeContact FinishGoldContact Finish ThicknessJoin (0.76µm)Contact TypeJoin (0.76µm)Color-Fange Features-Forge FeaturesSolgen SentenceContact TypeBoyshor BronzeContact Finish ThicknessGoldContact Finish ThicknessSolgen SentenceColor-Fange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-Solder Catter Sentence-		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact Material9osphor BronzeContact Finish ThicknessGoldContact Finish ThicknessJour (0.76µm)Contact Finish ThicknessGoldContact Finish ThicknessHosp BellowsColor-Fange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type0.100" (2.54mm)Contact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Fange Features-Forge Features-Color-Contact TypeColor SolderColor-Color-Fange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-	Series	-	
Number of Positions/Bay/Row6Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type100" (2.54mm)TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeLoop BellowsColor-Flange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions12Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeLoop BellowsColor-Flange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeLoop BellowsColor-Flange FeatureFush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	6	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	12	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleMounting TypeSolderTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness30µin (0.76µm)Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeLoop BellowsColor-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
Color-Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureFlush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Loop Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-	
	Flange Feature	Flush Mount, Side Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report erro	Operating Temperature	-65°C ~ 125°C	
		Rep	ort errors?

ECC06DTAZ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC06DTAZ Payment Methods



ECC06DTAZ Shipping Methods



If you have any question about ECC06DTAZ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com