



# **ECC08DCBS Information**

Heisener.com

Part Number ECC08DCBS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 16POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ECC08DCBS Specifications**

| Manufacturer Part Number         ECC08DCBS           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30µin (0.76µm)           Cotact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C | Lecool CB5 Specifications   |   |
|--|-----------------------------|---|
| Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C  | Manufacturer Part Number    | ECC08DCBS   |
| Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Manufacturer                | Sullins Connector Solutions                         |
| Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C   | Category                    | Connectors, Interconnects                           |
| Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness $0.062"$ (1.57mm)Number of Rows2Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30\mu$ in (0.76 $\mu$ m)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65^{\circ}$ C ~ 125°C   |                             | Card Edge Connectors - Edgeboard Connectors         |
| Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row8Number of Positions16Card Thickness $0.062"$ (1.57mm)Number of Rows2Pitch $0.100"$ (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30\mu$ in (0.76 $\mu$ m)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65^{\circ}$ C ~ 125°C  | Package                     | -   |
| Gender         Female           Number of Positions/Bay/Row         8           Number of Positions         16           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole, Right Angle           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C  | Series                      | -   |
| Number of Positions/Bay/Row8Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Card Type                   | Non Specified - Dual Edge                           |
| Number of Positions16Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Gender                      | Female  |
| Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Number of Positions/Bay/Row | 8   |
| Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Number of Positions         | 16  |
| Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C  | Card Thickness              | 0.062" (1.57mm)                                     |
| Features  Mounting Type Through Hole, Right Angle  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Contact Finish Thickness 30μin (0.76μm)  Contact Type Hairpin Bellows  Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C   | Number of Rows              | 2   |
| Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C   | Pitch                       | 0.100" (2.54mm)                                     |
| Termination Solder  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$  | Features                    | -   |
| Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$  | Mounting Type               | Through Hole, Right Angle                           |
| Contact Finish  Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type  Hairpin Bellows  Color  - Flange Feature  Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature  -65°C ~ 125°C  | Termination                 | Solder  |
| Contact Finish Thickness $30\mu in (0.76\mu m)$<br>Contact Type Hairpin Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia  Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$  | Contact Material            | Phosphor Bronze                                     |
| Contact Type Hairpin Bellows  Color -  Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C   | Contact Finish              | Gold  |
| Color - Side Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature - $65$ °C ~ $125$ °C  | Contact Finish Thickness    | 30μin (0.76μm)                                      |
| Flange Feature Side Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C   | Contact Type                | Hairpin Bellows                                     |
| Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$   | Color                       | -   |
|  | Flange Feature              | Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia |
| Report errors?   | Operating Temperature       | -65°C ~ 125°C                                       |
|  |                             | Report errors?                                      |

### **ECC08DCBS Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ECC08DCBS Payment Methods**



















## **ECC08DCBS Shipping Methods**













If you have any question about ECC08DCBS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com