

ECC13DKAH

ECC13DKAH Information

Heisener.com	Part Number Manufacturer Category Description Package	ECC13DKAH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 26POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECC13DKAH Specifications

ManufacturerSullins Connector SolutionsCardegeroyConnectors, Ledgeboard ConnectorsPackage-Package-Stries-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions0602° (1.57mm)Number of Rows0.602° (1.57mm)Number of Rows0.100° (2.54mm)Features-Mounting Type0.100° (2.54mm)Contact MaterialSolderContact FinishGoldContact FinishGoldContact FinishGoldContact TypeGuin (0.76µm)Contact TypeGuin (0.76µm)Contact Finish ThicknessGuin (0.76µm)Contact Finish ThicknesGuin (0.76µm)Contact Finish ThicknesGuin (0.76µm)Contact Finish ThicknesGuin (0.76µm)Contact Finish ThicknesGuin (0.76µm) <td< th=""><th>_</th><th></th></td<>	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Stries-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Mounting TypeMonghe Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness0.0010 (0.54mm)Contact TypeGoldContact Finish ThicknessSolderContact Finish Thickness0.010 (0.76µm)Contact Finish Thickness0.010 (0.76µm)Contact TypeCantileverColor-Flange FeatureNopont Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	ECC13DKAH
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 13 Number of Positions 26 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Mounting Type - Mounting Type Through Hole, Right Angle Contact Material Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Contact Type Cantilever Contact Type Cantilever Contact Type - Contact Type Cantilever Contact Type Cantilever Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature 65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverContact TypeCantileverFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeOtolou" (Angel Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact Type-Flange Feature-Flange FeatureContact Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact TypeGoldContact TypeOujon (0.76µm)Color-Flange Feature-Forge Feature-Forge Feature-Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row13Number of Positions26Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeOlderTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 26 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Cortact Material Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeGuhi (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	13
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	26
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ECC13DKAH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC13DKAH Payment Methods



ECC13DKAH Shipping Methods



If you have any question about ECC13DKAH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com