

ECC24DKRH

ECC24DKRH Information

Heisener.com	Part Number Manufacturer Category Description Package	ECC24DKRH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 48POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECC24DKRH Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeMon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions0602° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)FeaturesGolderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish ThicknessGoldContact TypeGoldContact TypeSilvin (0.76µm)Contact TypeSilvin (0.76µm)Contact Finish ThicknessSilvin (0.76µm)Contact TypeContifientSolipeSilvin (0.76µm)Contact TypeSilvin (0.76µm)Contact TypeSilvin (0.76µm)Contact TypeContifientSoliperSilvin (0.76µm)Contact TypeSilvin (0.76µm)Contact Ty	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions/Bay/Row0602° (1.57mm)Number of Rows0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)FeaturesGoard Edge, Straddle MountMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact TypeGoaldContact TypeSoldierContact TypeSoldierContact TypeSoldierContact TypeSoldierContact TypeGoaldContact TypeSolphonzeContact TypeSolphonzeContact TypeSolphonzeContact TypeSolphonzeColphage FeatureTop Mount Opening, Unthreaded, 0.125° (3.18mm) DiaOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	ECC24DKRH
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCard lieverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCard lieverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact FinishSolderContact Finish Thickness30µin (0.76µm)Contact TypeCard ExtenderPitch100° (2.54mm)FeaturesSolderContact Finish ThicknessSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact Type-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialSolderContact Finish ThicknessGoldContact TypeGoldContact TypeSoldierContact TypeGoldContact TypeGoldContact TypeGoldContact TypeContalieverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row24Number of Positions48Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCard IleverColor-Flarge FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 48 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact Type-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	24
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	48
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	-
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ECC24DKRH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC24DKRH Payment Methods



ECC24DKRH Shipping Methods



If you have any question about ECC24DKRH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com