



### **ECC30DSXH Information**

Heisener.com

Part Number ECC30DSXH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 60POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ECC30DSXH Specifications**

Manufacturer Part Number         ECC30DSXH           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         60           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30µin (0.76µm)           Contact Type         Full Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Le C30D52XII Specifications	
Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         60           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Full Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Manufacturer Part Number	ECC30DSXH
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         60           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Full Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         -           Number of Positions         60           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Full Bellows           Color         -           Flange Feature         Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row-Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row       -         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       -         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions       60         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Finish Thickness       30μin (0.76μm)         Contact Type       Full Bellows         Color       -         Flange Feature       Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia         Operating Temperature       -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	-
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	60
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole  Termination Solder  Contact Material Phosphor Bronze  Contact Finish Contact Finish Thickness 30μin (0.76μm)  Contact Type Full Bellows  Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia  Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, $0.125$ " (3.18mm) DiaOperating Temperature $-65$ °C ~ $125$ °C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature $-65$ °C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30μin (0.76μm)$ Contact TypeFull BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, $0.125" (3.18mm)$ DiaOperating Temperature $-65$ °C ~ $125$ °C	Mounting Type	Through Hole
Contact Finish  Contact Finish Thickness $30\mu$ in $(0.76\mu$ m)  Contact Type  Full Bellows  Color  -  Flange Feature  Top Mount Opening, Unthreaded, $0.125$ " $(3.18$ mm) Dia  Operating Temperature  -65°C ~ $125$ °C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Full Bellows Color - Top Mount Opening, Unthreaded, $0.125''$ ( $3.18mm$ ) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Full Bellows  Color - Top Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia  Operating Temperature $-65$ °C $\sim 125$ °C	Contact Finish	Gold
Color - Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Unthreaded, $0.125$ " ( $3.18$ mm) Dia Operating Temperature $-65$ °C $\sim 125$ °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors

#### **ECC30DSXH Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ECC30DSXH Payment Methods**



















## **ECC30DSXH Shipping Methods**













If you have any question about ECC30DSXH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com