



# **ECC35DKDI Information**

Heisener.com

Part Number ECC35DKDI

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 70POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **ECC35DKDI Specifications**

Manufacturer Part Number         ECC35DKDI           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30µin (0.76µm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	Ecc33DIXDI Specifications	
Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       35         Number of Positions       70         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.100" (2.54mm)         Features       -         Mounting Type       Through Hole         Termination       Solder         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Type       Cantilever         Color       -         Flange Feature       Top Mount Opening, Threaded Insert, 4-40         Operating Temperature       -65°C ~ 125°C	Manufacturer Part Number	ECC35DKDI
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions Number of Positions Number of Positions Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color - Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature Color Termination Type Contact Turned Threaded Insert, 4-40 Operating Temperature - 65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30µin (0.76µm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-
Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.100" (2.54mm)           Features         -           Mounting Type         Through Hole           Termination         Solder           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         30μin (0.76μm)           Contact Type         Cantilever           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	35
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	70
Pitch0.100" (2.54mm)Features-Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features  Mounting Type Through Hole Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color - Flange Feature Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough HoleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
Termination  Solder  Contact Material  Phosphor Bronze  Contact Finish  Gold  Contact Finish Thickness  30μin (0.76μm)  Contact Type  Cantilever  Color  - Flange Feature  Top Mount Opening, Threaded Insert, 4-40  Operating Temperature  Solder	Features	-
Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $30\mu$ in $(0.76\mu$ m)  Contact Type Cantilever  Color -  Flange Feature Top Mount Opening, Threaded Insert, 4-40  Operating Temperature $-65^{\circ}$ C $\sim 125^{\circ}$ C	Mounting Type	Through Hole
Contact Finish  Contact Finish Thickness  30 $\mu$ in (0.76 $\mu$ m)  Contact Type  Cantilever  Color  Flange Feature  Top Mount Opening, Threaded Insert, 4-40  Operating Temperature  -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Cantilever $-$ Color $-$ Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Color Color Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color - Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

### **ECC35DKDI Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ECC35DKDI Payment Methods**



















# **ECC35DKDI Shipping Methods**













If you have any question about ECC35DKDI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com