



ECC44DCCS Information

Heisener.com

Part Number ECC44DCCS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 88POS 0.100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECC44DCCS Specifications

Manufacturer Part Number ECC44DCCS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Ecc+4D ccb specifications	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	ECC44DCCS
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness $0.062" (1.57 mm)$ Number of Rows2Pitch $0.100" (2.54 mm)$ Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $30 \mu in (0.76 \mu m)$ Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, $0.125" (3.18 mm)$ DiaOperating Temperature $-65°C \sim 125°C$	Series	-
Number of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	44
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	88
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 30μ in $(0.76\mu$ m)Contact TypeHairpin BellowsColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125 " (3.18mm) DiaOperating Temperature -65 °C ~ 125 °C	Pitch	0.100" (2.54mm)
Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Features	-
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Mounting Type	Through Hole, Right Angle
Contact Finish Gold Contact Finish Thickness 30 μ in (0.76 μ m) Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Solder
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Hairpin Bellows Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color - Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30μin (0.76μm)
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18 mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ECC44DCCS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC44DCCS Payment Methods



















ECC44DCCS Shipping Methods













If you have any question about ECC44DCCS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com