



ECC50DKUS Information

Heisener.com

Part Number ECC50DKUS

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 100POS .100

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECC50DKUS Specifications

Manufacturer Part Number ECC50DKUS Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Eccsobico specifications		
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	ECC50DKUS	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects	
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row50Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row 50 Number of Positions 100 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions100Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	50	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	100	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features Mounting Type Through Hole, Right Angle Termination Solder Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 30μin (0.76μm) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
Termination Solder Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Features	-	
Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) Dia Operating Temperature -65 °C ~ 125 °C	Mounting Type	Through Hole, Right Angle	
Contact Finish Gold Contact Finish Thickness 30μ in $(0.76\mu$ m) Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125 " $(3.18mm)$ Dia Operating Temperature -65 °C ~ 125 °C	Termination	Solder	
Contact Finish Thickness $30\mu in (0.76\mu m)$ Contact Type Cantilever Color - Side Mount Opening, Unthreaded, $0.125''$ ($3.18mm$) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze	
Contact Type Cantilever Color - Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold	
Color - Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30μin (0.76μm)	
Flange Feature Side Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Cantilever	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-	
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
Report criois:			Report errors?

ECC50DKUS Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC50DKUS Payment Methods



















ECC50DKUS Shipping Methods













If you have any question about ECC50DKUS, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com