

ECC70DKAH

ECC70DKAH Information

Heisener.com	 ECC70DKAH Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 140POS .100 - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECC70DKAH Specifications

Manufacturer Part Number ECC70DKAH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Package - Stries - Gender Non Specified Polated Connectors Grad Type - Gender Female Number of Positions/Bay/Row 70 Number of Positions/Bay/Row 70 Number of Positions 140 Striks 0.062"(1.57mm) Number of Rows 2 Pictures 0.100"(2.54mm) Number of Rows 2 Pictures - Mounting Type Nogher Honspecter Contact Material Solder Contact Material Solder Contact Finish Thickness Gold Contact Finish Thickness Solido: Solid		
CatagoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nounting Type0.100° (2.54mm)Contact FinishSolderContact FinishSolderContact Finish Thickness0.910 (0.76µm)Contact Finish Thickness3µin (0.76µm)Contact TypeCantileverContact Finish Thickness0.920 (0.76µm)Contact Finish Thickness0.910 (0.76µm)Contact TypeCantileverContact Type	Manufacturer Part Number	ECC70DKAH
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type100" (2.54mm)Contact MaterialSolderContact MaterialGoldContact FinishGoldContact Finish Thickness3ujai (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.662" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type70Contact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverContact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Finish ThicknessGoldContact Type-Features-Contact TypeGrout Orgening. Unthreaded, 0.125" (3.18mm) DiaColor-Features-Color-Color-Color-FeatureSolor Contact Sinsin ThicknessColor-Color-FeatureSindout Opening. Unthreaded, 0.125" (3.18mm) DiaColor-Contact Type-Color-Feature-Color-Feature-Color-Feature-Color-Color-Color-Feature-Color-Color-Color-Color-Color-Color-Color-Color-Color-Color-<		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65° C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact Finish ThicknessGoldContact Finish Thickness50µin (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-Mounting TypeSolderContact MaterialSolderContact FinishGoldContact Finish ThicknessGoldContact Type-Contact TypeCantileverFlange Feature-Forge FeatureSolderOpening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature-SolderOpening, Unthreaded, 0.125" (3.18mm) Dia	Card Type	Non Specified - Dual Edge
Number of Positions 140 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type - Mounting Type Through Hole, Right Angle Contact Material Solder Contact Finish Gold Contact Finish Thickness 30µin (0.76µm) Contact Type Cantilever Flange Feature - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	70
Number of Rows2Nitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	140
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact Type-Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJujin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness30μin (0.76μm)Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeCantileverColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Cantilever
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$
		Report errors?

ECC70DKAH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC70DKAH Payment Methods



ECC70DKAH Shipping Methods



If you have any question about ECC70DKAH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com