

ECC70DPUH

uest a Quote

ECC70DPUH Information

Heisener.com	Part Number	ECC70DPUH	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 140POS .100	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECC70DPUH Specifications

Manufacturer Part Number ECC70DPUH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package Card Edge Connectors - Edgeboard Connectors Package - Stries - Card Type Mon Specified Polard Edge Gender Female Number of Positions/Bay/Row 70 Number of Positions/Bay/Row 70 Number of Positions/Bay/Row 140 Striks 0.062" (1.57mm) Number of Rows 2 Pitch 1.00" (2.54mm) Nouting Type Solder Young Hole, Right Angle Solder Contact Material Solder Contact Finish Thickness Solder Contact Finish Thickness Soldin Gomy Contact Type JunipenBlows Contact Type Soly (5.6mm) Contact Finish Thickness Solidor (5.6mm) Contact Type Solidor (5.6mm) Contact Type<	_		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062° (1.57mm)Number of Rows2Pitch0.100° (2.54mm)Features-Nounging TypeMing Hole, Right AngleContact FinishSolderContact FinishGoldContact Finish Thickness3µin (0.76µm)Contact Finish ThicknessSilpellowsColor-FauresSilpellowsContact Finish ThicknessSilpellowsContact Finish ThicknessSilpellowsColor-FauresSilpellowsColor-FauresSilpellowsColor-Color-FauresSilpellowsColor-Color-FauresSilpellowsColor-Color-FauresSilpellowsColor-FauresSilpellowsColor-FauresSilpellowsColor-FauresSilpellowsColor-FauresSilpellowsColor-FauresSilpellowsColor-FauresSilpellowsColor-Faures <td>Manufacturer Part Number</td> <td colspan="2">ECC70DPUH</td>	Manufacturer Part Number	ECC70DPUH	
AckageCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Card Thickness0.062" (1.57mm)Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeNonge Hole, Right AngleTerminationSolderCortact MaterialGoldContact Finish Thickness30jai (0.76µm)Contact Finish Thickness30jai (0.76µm)Coltact TypeHarjin BellowsColtar Finish Thickness-Coltar TypeGoldColtar TypeSolder SolderColtar TypeSolder Solder SolderColtar TypeSolder Solder	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.662" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type70Contact MaterialSolderContact FinishGoldContact Finish Thickness3upin (0.76µm)Contact TypeJapin BellowsColor-FeaturesGoldContact TypeHairpin BellowsColor-Finage FeatureGondout Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeHairpin BellowsColor-Flange FeatureGroMountOpening, Unthreaded, 0.125" (3.18mm) DiaOpenting Temperature65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact Type-Flange Feature-Flange FeatureContact Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65° c~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row70Number of Positions140Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish ThicknessJuin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureContact Opening, Unthreaded, 0.125" (3.18mm) DiaOpenating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 140 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Through Hole, Right Angle Termination Solder Contact Material Posphor Bronze Contact Finish Gold Contact Type Hairpin Bellows Color - Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeJuni (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Number of Positions/Bay/Row	70	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	140	
Pitch0.100" (2.54mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature65°C ~ 125°C	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder	
Contact Finish Thickness30μin (0.76μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
Color-Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Hairpin Bellows	
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	-65°C ~ 125°C	
		Report errors	

ECC70DPUH Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECC70DPUH Payment Methods



ECC70DPUH Shipping Methods



If you have any question about ECC70DPUH, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com