

# ECE-A0JN470UB

est a Quote

### **ECE-A0JN470UB Information**

Heisener.com	Part Number	ECE-A0JN470UB
	Manufacturer	Panasonic Electronic Components
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 47UF 20% 6.3V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com E-mail: salesdept@heisener.com

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **ECE-A0JN470UB** Specifications

Manufacturer Part Number ECE-A0JN470UB   Manufacturer Panasonic Electronic Components   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can   Series SU   Capacitance 47µF   Tolerance ±20%   Voltage - Rated 5.0   ESR (Equivalent Series Resistance) -   Lifetime @ Temp. 2000 Hrs @ 85°C   Operating Temperature -40°C - 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance -   Lipsdy Seried (Max) -   Size / Dimension -		
Category Capacitors   Aluminum Electrolytic Capacitors   Package Radial, Can   Series SU   Capacitance 47µF   Tolerance ±20%   Voltage - Rated 6.3V   ESR (Equivalent Series Resistance) -   Lifetime @ Temp. 2000 Hrs @ St°C   Operating Temperature 40°C ~ 85°C   Polarization Bi-Polar   Applications General Purpose   Ripple Current - High Frequency -   Impedance -   Liad Spacing -   Ster / Dimension -   Hight - Seated (Max) -   Surface Mount Land Size -   Mounting Type Irough Hole	Manufacturer Part Number	ECE-A0JN470UB
AckageAluninum Electrolytic CapacitorsPackageRadial, CanSeriesSUCapacitance47µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lided Spacing-Size / Dimension-Size / Dimension-Starface (Max)-Surface Mount Land Size-Hounting TypeMounting TypePackage / CaseRadial, Can	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesSUCapacitance47μFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications6.31Ripple Current - Low Frequency-Lifeting @ Jamesing153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Hounting Type-Package / Case-	Category	Capacitors
SeriesSUCapacitance47µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - High Frequency153mA @ 10kHzImpedance-Liad Spacing-Size / Dimension-Hight - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / Case-Reade Size / Case-		Aluminum Electrolytic Capacitors
Capacitance47µFTolerance±20%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRippe Current - High Frequency153mA @ 10kHzInpedance-Karde J Starde Maximum-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mouning TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature4.0°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing-Size / Dimension-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / Case-Stafe Age-Stafe Age-	Series	SU
Voltage - Rated6.3VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Inpedance-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / CaseStail, Can	Capacitance	47µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / Case-Ringe / Ringe / Case-Ringe / Ringe /	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	6.3V
Operating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting Type-Package / CaseRadia, Can	ESR (Equivalent Series Resistance)	-
PolarizationBi-PolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThroug HolePackage / CaseRadia, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency-Ripple Current - High Frequency153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Bi-Polar
Ripple Current - High Frequency153mA @ 10kHzImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
In rest of restImpedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	153mA @ 10kHz
Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	-
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	-
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	-
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
Report enois.		Report errors?

#### **ECE-A0JN470UB** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **ECE-A0JN470UB Payment Methods**



## **ECE-A0JN470UB Shipping Methods**



If you have any question about ECE-A0JN470UB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com