



ECE-V1CA470SP Information



For Reference Only

Part Number ECE-V1CA470SP

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 16V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECE-V1CA470SP Specifications

Manufacturer Part Number ECE-V1CA470SP Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series VS Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	1	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series VS Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Manufacturer Part Number	ECE-V1CA470SP
PackageRadial, Can - SMDSeriesVSCapacitance47μFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency70mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.213" (5.40mm)Surface Mount Land Size0.260" L x 0.260" W (6.60mm x 6.60mm)	Manufacturer	Panasonic Electronic Components
Package Radial, Can - SMD Series VS Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Category	Capacitors
Series VS Capacitance 47µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)		Aluminum Electrolytic Capacitors
Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Series	VS
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size 16V 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size -2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~ 80°C ~ 80°C -40°C ~ 80°C -40°C ~ 80°C ~ 80°C -40°C ~ 80°C -40°	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size 2000 Hrs @ 85°C -40°C ~ 85°C Polar General Purpose	Voltage - Rated	16V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose 70mA @ 120Hz 70mA @ 120Hz Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size General Purpose 70mA @ 120Hz - 0.248" Dia (6.30mm) 0.248" Dia (6.30mm) 0.213" (5.40mm) 0.260" L x 0.260" W (6.60mm x 6.60mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 70mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Ripple Current - Low Frequency	70mA @ 120Hz
Lead Spacing - Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Impedance	-
Height - Seated (Max) 0.213" (5.40mm) Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Lead Spacing	-
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)	Size / Dimension	0.248" Dia (6.30mm)
	Height - Seated (Max)	0.213" (5.40mm)
	Surface Mount Land Size	0.260" L x 0.260" W (6.60mm x 6.60mm)
Mounting Type Surface Mount	Mounting Type	Surface Mount
Package / Case Radial, Can - SMD	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

ECE-V1CA470SP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECE-V1CA470SP Payment Methods



















ECE-V1CA470SP Shipping Methods













If you have any question about ECE-V1CA470SP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com