

ECH-S1H222JZ

ECH-S1H222JZ Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECH-S1H222JZ Specifications

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECHS(Z)Capacitance2200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 125°CMounting TypeThrough HoleSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Manufacturer Part Number	ECH-S1H222JZ
Film CapacitorsPackageRadialSeriesECHS(Z)Capacitance2200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 125°CMounting TypeThrough HoleSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECHS(Z)Capacitance2200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 125°CMounting Type11rough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Category	Capacitors
Series ECHS(Z) Capacitance 2200pF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 50V Dielectric Material Polyphenylene Sulfide (PPS) Dielectric Material - Operating Temperature -40°C ~ 125°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.335" L x 0.158" W (8.50mm x 4.00mm) Height - Seated (Max) 0.346" (8.80mm) Termination PC Pins Lead Spacing 0.197" (5.00mm) Applications High Frequency, Switching		Film Capacitors
Capacitance200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 125°CMounting TypeRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Size / Dimension0.346" (8.80mm)Height - Seated (Max)0.346" (5.00mm)Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 125°CMounting TypeThrough HoleSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)O.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Series	ECHS(Z)
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)OP PinsTerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Capacitance	2200pF
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Tolerance	±5%
Dielectric MaterialPolyphenylene Sulfide (PPS)ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Voltage Rating - DC	50V
Operating Temperature-40°C ~ 125°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Dielectric Material	Polyphenylene Sulfide (PPS)
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.335" L x 0.158" W (8.50mm x 4.00mm)Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Operating Temperature	-40°C ~ 125°C
Size / Dimension 0.335" L x 0.158" W (8.50mm x 4.00mm) Height - Seated (Max) 0.346" (8.80mm) Termination PC Pins Lead Spacing 0.197" (5.00mm) Applications High Frequency, Switching	Mounting Type	Through Hole
Height - Seated (Max)0.346" (8.80mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Package / Case	Radial
TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Size / Dimension	0.335" L x 0.158" W (8.50mm x 4.00mm)
Lead Spacing0.197" (5.00mm)ApplicationsHigh Frequency, Switching	Height - Seated (Max)	0.346" (8.80mm)
Applications High Frequency, Switching	Termination	PC Pins
	Lead Spacing	0.197" (5.00mm)
Features -	Applications	High Frequency, Switching
	Features	-
Report errors?		Report errors?

ECH-S1H222JZ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECH-S1H222JZ Payment Methods



ECH-S1H222JZ Shipping Methods



If you have any question about ECH-S1H222JZ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com