

ECH-U1C122JX5

ote

ECH-U1C122JX5 Information

www.helsenfic.com	Part Number Manufacturer Category Description Package	ECH-U1C122JX5 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 1200PF 5% 16VDC 0603 0603 (1608 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quot

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECH-U1C122JX5 Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackage0603 (1608 Metric)SeriesECH-U(X)Capacitance1200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.033" (0.85mm)Height - Seated (Max)-ApplicationsSolder PadsLead Spacing-ApplicationsGeneral Purpose			
CategoryCapacitorsFilm CapacitorsPackage0603 (1608 Metric)SeriesECH-U(X)Capacitance1200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063° L x 0.031° W (1.60mm x 0.80mm)Height - Seated (Max)0.033° (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-Starten Metric Constructions-Solder Pads-Applications-Starten Metric Constructions-Solder Pads-Applications-Starten Metric Constructions-Solder Pads-Starten Metric Constructions-Solder Pads-Case-Starten Metric Constructions-Solder Starten Metric Constructions-Starten Metric Constructions-Solder Starten Metric Constructions-Starten Metric Constructions-Starten Metric Constructions-Starten Metric Constructions-Starten Metric Constructions-Starten Metric Constructions-	Manufacturer Part Number	ECH-U1C122JX5	
Film CapacitorsPackage0603 (1608 Metric)SeriesECH-U(X)Capacitance1200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-Features-Features-	Manufacturer	Panasonic Electronic Components	
Package0603 (1608 Metric)SeriesECH-U(X)Capacitance1200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Category	Capacitors	
SeriesECH-U(X)Capacitance1200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-		Film Capacitors	
Capacitance1200pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	0603 (1608 Metric)	
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	ECH-U(X)	
Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	1200pF	
Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±5%	
Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	16V	
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyphenylene Sulfide (PPS), Metallized - Stacked	
Mounting TypeSurface MountPackage / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case0603 (1608 Metric)Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension0.063" L x 0.031" W (1.60mm x 0.80mm)Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)0.033" (0.85mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	0603 (1608 Metric)	
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)	
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.033" (0.85mm)	
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	General Purpose	
Report errors?	Features	-	
		Reg	port errors?

ECH-U1C122JX5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECH-U1C122JX5 Payment Methods



ECH-U1C122JX5 Shipping Methods



If you have any question about ECH-U1C122JX5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com