

ECH-U1C333GX5

ECH-U1C333GX5 Information

www.helsener.com	 ECH-U1C333GX5 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.033UF 2% 16VDC 1206 1206 (3216 Metric) For the pricing/inventory/lead time_please contact	
For Reference Only	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECH-U1C333GX5 Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsPackage1206 (3216 Metric)PackageECH-U(X)Capacitance0.033µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating TemperatureSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)		
CategoryCapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesECH-U(X)Capacitance0.033µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Manufacturer Part Number	ECH-U1C333GX5
Film CapacitorsPackage1206 (3216 Metric)SeriesECH-U(X)Capacitance0.033µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Manufacturer	Panasonic Electronic Components
Package1206 (3216 Metric)SeriesECH-U(X)Capacitance0.033μFTolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Category	Capacitors
SeriesECH-U(X)Capacitance0.033µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)		Film Capacitors
Capacitance0.033 μFTolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Package	1206 (3216 Metric)
Tolerance±2%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Series	ECH-U(X)
Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Capacitance	0.033µF
Voltage Rating - DC16VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Tolerance	±2%
Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Voltage Rating - DC	16V
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Dielectric Material	Polyphenylene Sulfide (PPS), Metallized - Stacked
Mounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	ESR (Equivalent Series Resistance)	-
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)	Mounting Type	Surface Mount
	Package / Case	1206 (3216 Metric)
Height - Seated (Max) 0.051" (1.30mm)	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
	Height - Seated (Max)	0.051" (1.30mm)
Termination Solder Pads	Termination	Solder Pads
Lead Spacing -	Lead Spacing	-
Applications General Purpose	Applications	General Purpose
Features -	Features	-
Report errors?		Report errors?

ECH-U1C333GX5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECH-U1C333GX5 Payment Methods



ECH-U1C333GX5 Shipping Methods



If you have any question about ECH-U1C333GX5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com