

# ECH-U1H153GX5

#### **ECH-U1H153GX5 Information**

	Part Number	ECH-U1H153GX5	
		Panasonic Electronic Components	同の思わる
www.heisener.com	Category	Capacitors Film Capacitors	E2 (04 (01 E)
	Description	CAP FILM 0.015UF 2% 50VDC 1210	- <b>X36225</b> 55
	Package	1210 (3225 Metric)	
		For the pricing/inventory/lead time, please contact us	E 224 774
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## ECH-U1H153GX5 Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackage1210 (3225 Metric)SeriesECH-U(X)Capacitance0.015µFTolerance±2%Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature50°C ~ 125°CVoltage / Case1210 (3225 Metric)Size / Dinension0.0120° L x 0.098° W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-Statement- <trt< th=""><th></th><th></th></trt<>		
CategoryCapacitorsFilm CapacitorsPackage1210 (3225 Metric)SeriesECH-U(X)Capacitance0.015µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.051" (1.30mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-Capacitons-Capacitons-Surface Mount-Size / Dimension0.51" (1.30mm)TerminationSolder PadsLead Spacing-Surface Max-Surface Max-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-Capacitons-<	Manufacturer Part Number	ECH-U1H153GX5
Film CapacitorsPackage1210 (3225 Metric)SeriesECH-U(X)Capacitance0.015µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)Goler PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer	Panasonic Electronic Components
Package1210 (325 Metric)SeriesECH-U(X)Capacitance0.015µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating TemperatureSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Category	Capacitors
SeriesECH-U(X)Capacitance0.015µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.051" (1.30mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-		Film Capacitors
Capacitance0.015µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.051" (1.30mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-Features-	Package	1210 (3225 Metric)
Tolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	ECH-U(X)
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	0.015µF
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±2%
Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyphenylene Sulfide (PPS), Metallized - Stacked
Mounting TypeSurface MountPackage / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / Case1210 (3225 Metric)Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C
Size / Dimension0.126" L x 0.098" W (3.20mm x 2.50mm)Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount
Height - Seated (Max)0.051" (1.30mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	1210 (3225 Metric)
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.051" (1.30mm)
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads
Features -	Lead Spacing	-
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

#### **ECH-U1H153GX5** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### ECH-U1H153GX5 Payment Methods



### ECH-U1H153GX5 Shipping Methods



If you have any question about ECH-U1H153GX5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com