

ECH-U1H154GC9

ECH-U1H154GC9 Information

www.helsener.com	 ECH-U1H154GC9 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.15UF 2% 50VDC 2416 2416 (6041 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECH-U1H154GC9 Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackage2416 (6041 Metric)SeriesECH-U(C)Capacitance0.15µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.02° (2.60mm)Height - Seated (Max)-TerminationSolder PadsLead Spacing-ApplicationsGeneral Purpose			
CategoryCapacitorsFilm CapacitorsPackage2416 (6041 Metric)SeriesECH-U(C)Capacitance0.15µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.123°C L x 0.161°W (6.00mm x 4.10mm)Height - Seated (Max)0.102° (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Manufacturer Part Number	ECH-U1H154GC9	
Film CapacitorsPackage2416 (6041 Metric)SeriesECH-U(C)Capacitance0.15μFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer	Panasonic Electronic Components	
Package2416 (6041 Metric)SeriesECH-U(C)Capacitance0.15µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236° L x 0.161° W (6.00mm x 4.10mm)Height - Seated (Max)0.102° (2.60mm)Lead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Category	Capacitors	
SeriesECH-U(C)Capacitance0.15μFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.102" (2.60mm) x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-Features-		Film Capacitors	
Capacitance0.15µFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.102" (2.60mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	2416 (6041 Metric)	
Tolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	ECH-U(C)	
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	0.15µF	
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±2%	
Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V	
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyphenylene Sulfide (PPS), Metallized - Stacked	
Nounting TypeSurface MountMounting TypeSurface MountPackage / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case2416 (6041 Metric)Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C	
Size / Dimension0.236" L x 0.161" W (6.00mm x 4.10mm)Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)0.102" (2.60mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	2416 (6041 Metric)	
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.236" L x 0.161" W (6.00mm x 4.10mm)	
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.102" (2.60mm)	
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	General Purpose	
Report errors?	Features	-	
		Repo	ort errors?

ECH-U1H154GC9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECH-U1H154GC9 Payment Methods



ECH-U1H154GC9 Shipping Methods



If you have any question about ECH-U1H154GC9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com