

ECH-U1H182JB5

ECH-U1H182JB5 Information

www.troisetto.com	Manufacturer	ECH-U1H182JB5 Panasonic Electronic Components	
	Category Description	Capacitors Film Capacitors CAP FILM 1800PF 5% 50VDC 0805	
	Package	0805 (2012 Metric)	- 26 John - 1
		For the pricing/inventory/lead time, please contact us	<u> </u>
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECH-U1H182JB5 Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackage0805 (2012 Metric)SeriesECH-U(B)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.039" (1.00mm)Height - Seated (Max)-ApplicationsSolder PadsLead Spacing-ApplicationsGeneral Purpose		
CategoryCapacitorsFilm CapacitorsPackage0805 (2012 Metric)SeriesECH-U(B)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.039" (1.00mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Manufacturer Part Number	ECH-U1H182JB5
Film CapacitorsPackage0805 (2012 Metric)SeriesECH-U(B)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.039" (1.00mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-Features-Features-	Manufacturer	Panasonic Electronic Components
Package0805 (2012 Metric)SeriesECH-U(B)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Category	Capacitors
SeriesECH-U(B)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Bieght - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-		Film Capacitors
Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	0805 (2012 Metric)
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	ECH-U(B)
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)Older PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	1800pF
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±5%
Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyphenylene Sulfide (PPS), Metallized - Stacked
Mounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C
Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount
Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	0805 (2012 Metric)
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.039" (1.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads
Features -	Lead Spacing	-
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

ECH-U1H182JB5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECH-U1H182JB5 Payment Methods



ECH-U1H182JB5 Shipping Methods



If you have any question about ECH-U1H182JB5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com